

BK/S505-V-10-R

BK/S505-V-10-R Information

r Eaton Circuit Protection Fuses FUSE CERAMIC 10A 250VAC 5X20MM 5mm x 20mm (Axial)	
us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote
	r Eaton Circuit Protection Fuses FUSE CERAMIC 10A 250VAC 5X20MM 5mm x 20mm (Axial) For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BK/S505-V-10-R Specifications

Manufacturer Part NumberBK/S505-V-10-RManufacturerEatonCategoryCircuit ProtectionCategoryFusesPackageSmm x 20mm (Axial)SeriesS505Fuse TypeCatridge, CeramicCurrent Rating10AVoltage Rating - ACS105Voltage Rating - DC-Response TimeSlowMounting TypeSinw 20mm (Axial)Mounting TypeSinw 20mm (Axial)Mounting TypeSinw 20mm (Axial)ApprovalsJSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Color0.218" Diax 0.831" L (5.54mm x 21.10mm)			
AnnominationInterferenceCategoryCircuit ProtectionFusesFusesPackage5mm x 20mm (Axial)SeriesS05Fuse TypeCartridge, CeramicCurrent Rating10AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Manufacturer Part Number	BK/S505-V-10-R	
FusesPackage5mm x 20mm (Axial)Series505Fuse TypeCartridge, CeramicCurrent Rating10AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseSmm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Manufacturer	Eaton	
PackageSmm x 20mm (Axial)SeriesS505Fuse TypeCartridge, CeramicFuse Type10ACurrent Rating250VVoltage Rating - AC50VVoltage Rating - DC-Response TimeSlowPackage / CaseSmm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage397ApprovalsSIS, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0218" Dia x 0.831" L (5.54mm x 21.10mm)	Category	Circuit Protection	
SeriesS505Fuse TypeCartridge, CeramicCurrent Rating10AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseSmm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)		Fuses	
Fuse TypeCartridge, CeramicFuse TypeCartridge, CeramicCurrent Rating10AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseSmm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color302Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Package	5mm x 20mm (Axial)	
Current Rating10AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseSimm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color3028" Dia x 0.831" L (5.54mm x 21.10mm)	Series	S505	
Voltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseSmm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Fuse Type	Cartridge, Ceramic	
Voltage Rating - DC-Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Current Rating	10A	
Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Voltage Rating - AC	250V	
Package / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Voltage Rating - DC	-	
Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Response Time	Slow	
Breaking Capacity @ Rated Voltage1.5kAMelting I2t397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Package / Case	5mm x 20mm (Axial)	
Melting I2t397ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Mounting Type	Through Hole	
ApprovalsBSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDEOperating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Breaking Capacity @ Rated Voltage	1.5kA	
Operating Temperature-Color-Size / Dimension0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Melting I2t	397	
Color - Size / Dimension 0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Approvals	BSI, CQC, CSA, cULus, IMQ, KC, PSE/JET, SEMKO, VDE	
Size / Dimension 0.218" Dia x 0.831" L (5.54mm x 21.10mm)	Operating Temperature	-	
	Color	-	
Papart arrors?	Size / Dimension	0.218" Dia x 0.831" L (5.54mm x 21.10mm)	
Report errors?			Report errors?

BK/S505-V-10-R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BK/S505-V-10-R Payment Methods





If you have any question about BK/S505-V-10-R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com