

BK1/ABC-7-R Information



For Reference Only

Part Number BK1/ABC-7-R

Manufacturer Eaton

Category Circuit Protection

Fuses

Description FUSE CERM 7A 250VAC 125VDC 3AB

Package 3AB, 3AG, 1/4" x 1-1/4"

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BK1/ABC-7-R Specifications

Manufacturer Part Number BKI/ABC-7-R Manufacturer Eaton Category Circuit Protection Package 3AB, 3AG, 1/4" x 1-1/4" Series ABC Fuse Type Cartridge, Ceramic Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A AC, 10kA DC Melting 12t 109.33 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm) Report errors?	*	
Category Circuit Protection Fuses Package 3AB, 3AG, 1/4" x 1-1/4" Series ABC Fuse Type Cartridge, Ceramic Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A AC, 10kA DC Melting I2t 109.33 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer Part Number	BK1/ABC-7-R
Fuses Package 3AB, 3AG, 1/4" x 1-1/4" Series ABC Fuse Type Cartridge, Ceramic Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A AC, 10kA DC Melting 12t 109.33 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer	Eaton
Package 3AB, 3AG, 1/4" x 1-1/4" Series ABC Fuse Type Cartridge, Ceramic Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A AC, 10kA DC Melting I2t 109.33 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Category	Circuit Protection
Series ABC Fuse Type Cartridge, Ceramic Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A AC, 10kA DC Melting 12t 109.33 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)		Fuses
Fuse Type Current Rating 7A Voltage Rating - AC Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t 109.33 Approvals Operating Temperature Color Size / Dimension Cartridge, Ceramic 7A Cartridge, Ceramic Capacity Cartridge, Ceramic Capacity TA Voltage Rating Capacity Approvals Capacity Capa	Package	3AB, 3AG, 1/4" x 1-1/4"
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t 109.33 Approvals CSA, UL Operating Temperature Color Size / Dimension 7A 7A 7A 250V 7A 7A 250V 7A 250V 70 125V 125V Response Time Fast 20A AC, 1/4" x 1-1/4" 109.33 CSA, UL 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Series	ABC
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting 12t Approvals CSA, UL Operating Temperature Color Size / Dimension 250V 125V 125	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t 109.33 Approvals CSA, UL Operating Temperature Color Size / Dimension 125V 125V 125V 109.33 CSA, UL 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Current Rating	7A
Response Time Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A AC, 10kA DC Melting I2t 109.33 Approvals CSA, UL Operating Temperature - Color Size / Dimension Fast 3AB, 3AG, 1/4" x 1-1/4" Holder 200A AC, 10kA DC - 109.33 - 109.3	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A AC, 10kA DC Melting I2t 109.33 Approvals CSA, UL Operating Temperature Color Size / Dimension 3AB, 3AG, 1/4" x 1-1/4" Holder 200A AC, 10kA DC CON AC, 10kA DC 109.33	Voltage Rating - DC	125V
Mounting Type Breaking Capacity @ Rated Voltage 200A AC, 10kA DC Melting I2t 109.33 Approvals CSA, UL Operating Temperature Color Size / Dimension Holder 200A AC, 10kA DC 109.33 CSA, UL 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Response Time	Fast
Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UL Operating Temperature Color Size / Dimension 200A AC, 10kA DC 109.33 CSA, UL - 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4"
Melting I2t 109.33 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Mounting Type	Holder
Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Breaking Capacity @ Rated Voltage	200A AC, 10kA DC
Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Melting I2t	109.33
Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Approvals	CSA, UL
Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Operating Temperature	-
, , , , , , , , , , , , , , , , , , ,	Color	-
Report errors?	Size / Dimension	0.250" Dia x 1.250" L (6.35mm x 31.75mm)
		Report errors?

BK1/ABC-7-R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BK1/ABC-7-R Payment Methods



















BK1/ABC-7-R Shipping Methods













If you have any question about BK1/ABC-7-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com