

BK1301-7R Information

Heisener.com

Part Number BK1301-7R

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERT 12V 12A

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BK1301-7R Specifications

| Manufacturer Part Number BK 1301-7R Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher K Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) Report errors? | | |
|--|--------------------------|--|
| Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher K Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Manufacturer Part Number | BK1301-7R |
| Package Module Series Melcher K Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Manufacturer | Bel Power Solutions |
| Package Module Series Melcher K Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Category | Power Supplies - External/Internal (Off-Board) |
| Series Melcher K Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | | DC DC Converters |
| Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Package | Module |
| Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Series | Melcher K |
| Voltage - Input (Max) 70V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Туре | Isolated |
| Number of Outputs 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Voltage - Input (Min) | 14V |
| Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 12V | Voltage - Input (Max) | 70V |
| Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension - Current - Output (Max) 12A Current - Output (Max) 150W Commercial), Railway Commer | Number of Outputs | 1 |
| Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) - Commercial), Railway - Co | Voltage - Output 1 | 12V |
| Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension -25°C ~ 31°C Chassis Mount Mounting Type Chassis Mount Mounting Type 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Voltage - Output 2 | - |
| Current - Output (Max) Power (Watts) Applications Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 12A 150W 1TE (Commercial), Railway -25°C ~ 71°C Chassis Mount 12A 150W 17E (Commercial), Railway 17E (Co | Voltage - Output 3 | - |
| Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 150W Applications ITE (Commercial), Railway -25°C ~ 71°C Chasilway -25°C ~ 71°C Chasilway -25°C ~ 71°C Module 150W 171 (Package / Case) Module 171 (171.0mm x 111.0mm x 80.0mm) | Voltage - Output 4 | - |
| Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Current - Output (Max) | 12A |
| Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Power (Watts) | 150W |
| Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Applications | ITE (Commercial), Railway |
| Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Operating Temperature | -25°C ~ 71°C |
| Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Efficiency | 82% |
| Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Mounting Type | Chassis Mount |
| | Package / Case | Module |
| Report errors? | Size / Dimension | 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) |
| | | Report errors? |

BK1301-7R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BK1301-7R Payment Methods



















BK1301-7R Shipping Methods













If you have any question about BK1301-7R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com