



BLED25W-150-C0160 Information

Part Number BLED25W-150-C0160
Manufacturer Thomas Research Products

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 21-36V 700MA

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BLED25W-150-C0160 Specifications

Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series BLED-25W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature -			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series BLED-25W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Manufacturer Part Number	BLED25W-150-C0160	
LED Drivers Package - Series BLED-25W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Manufacturer	Thomas Research Products	
Package - Series BLED-25W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series BLED-25W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)		LED Drivers	
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Series	BLED-25W	
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Туре	Constant Current	
Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Topology	AC DC Converter	
Voltage - Input (Max) Voltage - Output 21 ~ 36 V Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature Efficiency 89% Termination Style Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Number of Outputs	1	
Voltage - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max) 700mA Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Voltage - Input (Max)	305VAC	
Power (Watts) 25W Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Size / Dimension 25W - 25W - 84W - 84W 84W 85W 89% 89% 89% 89% 89% 89% 89% 89	Voltage - Output	21 ~ 36 V	
Voltage - Isolation - Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Current - Output (Max)	700mA	
Dimming - Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Power (Watts)	25W	
Features - Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Voltage - Isolation	-	
Ratings IP64 Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Dimming	-	
Operating Temperature - Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Features	-	
Efficiency 89% Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Ratings	IP64	
Termination Style Wire Leads Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Operating Temperature	-	
Size / Dimension 3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	Efficiency	89%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	3.44" L x 1.44" W x 0.94" H (87.5mm x 36.5mm x 24.0mm)	
		Report error	ors?

BLED25W-150-C0160 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BLED25W-150-C0160 Payment Methods



















BLED25W-150-C0160 Shipping Methods













If you have any question about BLED25W-150-C0160, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com