



BLP30-1005G Information

Heisener.com

Part Number BLP30-1005G Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 30W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BLP30-1005G Specifications

Manufacturer Part Number BLP30-1005G Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series BLP30 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	•		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series BLP30 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Manufacturer Part Number	BLP30-1005G	
Package - Series BLP30 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Manufacturer	Bel Power Solutions	
Package - Series BLP30 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series BLP30 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)		AC DC Converters	
Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Package	-	
Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Series	BLP30	
Voltage - Input Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Mounting Type Size / Dimension 100 ~ 250 VAC 5V CV CV SV SV SV SV SV SV SV S	Туре	Open Frame	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature DC Input Capable, Universal Input Mounting Type Size / Dimension 5V Current - Output (Max) - Current - Output (Max) 5A Over (Watts) 5D Commercial) 4.242kV (4242V) Efficiency Chassis Mount Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) 5A - Current - Output (Max) 5A 30W Applications ITE (Commercial) 4.242kV (4242V) Commercial) Features Commercial (With Derating) Commercial (With Derating) Commercial (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Voltage - Input	100 ~ 250 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) SA Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Company Samuel Size / Dimension Current - Output 4 - Chassis Mount - Chassis Moun	Voltage - Output 1	5V	
Voltage - Output 4 Current - Output (Max) 5A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Output 2	-	
Current - Output (Max) 5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Current - Output (Max)	5A	
Voltage - Isolation 4.242kV (4242V) Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Power (Watts)	30W	
Efficiency 75% Operating Temperature 0°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Applications	ITE (Commercial)	
Operating Temperature 0°C ~ 70°C (With Derating) DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Voltage - Isolation	4.242kV (4242V)	
Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Efficiency	75%	
Mounting Type Chassis Mount Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	
Size / Dimension 2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	Features	DC Input Capable, Universal Input	
	Mounting Type	Chassis Mount	
Report errors	Size / Dimension	2.07" L x 4.00" W x 1.07" H (52.6mm x 101.6mm x 27.2mm)	
Report crisis			Report errors?

BLP30-1005G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BLP30-1005G Payment Methods



















BLP30-1005G Shipping Methods













If you have any question about BLP30-1005G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com