

BLP40-1024G

a Quote

BLP40-1024G Information

Heisener.com	Part Number	BLP40-1024G	
	Manufacturer	Bel Power Solutions	िलिस
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	53
	Description	AC/DC CONVERTER 24V 40W	120
	Package	-	- 27
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reques

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BLP40-1024G Specifications

Manufacturer Bel Power Solutions Category Bel Power Supplies - External/Internal (Off-Board) Ac DC Converters AC DC Converters Package - Series BLP40 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Voltage - Output 4 - Voltage - Solution 1.1A Power (Watts) 40W Applications TE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input				
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series BLP40 Syries Series Number of Outputs I Voltage - Input 00 ~ 250 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Soltion 1.1A Power (Watts) 40W Applications TE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 0% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type	Manufacturer Part Number	BLP40-1024G		
AC DC Converters Package - Series BLP40 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.1A Power (Watts) 40W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.00° L x 5.00° W x 1.23° H (76.2mm x 127.0mm x 31.2mm)	Manufacturer	Bel Power Solutions		
Package-SeriesBLP40SpenOpen FrameNumber of Outputs1Voltage - Input100 ~ 250 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Power (Wats)40WApplicationsITE (Commercial)Voltage - Isolation-0%C ~ 70°C (With Derating)Operating TemperatureOic ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeSion" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series BLP40 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.1A Power (Watts) 40W Applications TE (Commercial) Voltage - Isolation 4.242kV (4242V) Operating Temperature 0%C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chasis Mount Size / Dimension 3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)		AC DC Converters		
Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 4 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 6 - Voltage - Solation 1.1A Voltage - Isolation 4.242kV (4242V) Efficiency 70% Voltage - Isolation 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2	Package	-		
Number of Outputs 1 Voltage - Input 100 ~ 250 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.1A Power (Watts) 40W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Series	BLP40		
Voltage - Input 100 ~ 250 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.1A Power (Watts) 40W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 0°C ~ 70°C (With Derating) Peatures Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Туре	Open Frame		
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.1A Power (Watts) 40W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Size / Dimension	Number of Outputs	1		
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.1A Power (Watts) 40W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 70% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Voltage - Input	100 ~ 250 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)1.1APower (Watts)40WApplicationsITE (Commercial)Voltage - Isolation4.242kV (4242V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Voltage - Output 1	24V		
Voltage - Output 4-Current - Output (Max)1.1APower (Watts)40WApplicationsITE (Commercial)Voltage - Isolation4.242kV (4242V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Voltage - Output 2	-		
Current - Output (Max)1.1APower (Watts)40WApplicationsITE (Commercial)Voltage - Isolation4.242kV (4242V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)PeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Voltage - Output 3	-		
Power (Watts)40WApplicationsITE (Commercial)Voltage - Isolation4.242kV (4242V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation4.242kV (4242V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Current - Output (Max)	1.1A		
Voltage - Isolation4.242kV (4242V)Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Power (Watts)	40W		
Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Applications	ITE (Commercial)		
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Voltage - Isolation	4.242kV (4242V)		
FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Efficiency	70%		
Mounting TypeChassis MountSize / Dimension3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Operating Temperature	0° C ~ 70° C (With Derating)		
Size / Dimension 3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)	Features	Adjustable Output, Remote Sense, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	3.00" L x 5.00" W x 1.23" H (76.2mm x 127.0mm x 31.2mm)		
			Report errors?	

BLP40-1024G Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BLP40-1024G Payment Methods



BLP40-1024G Shipping Methods



If you have any question about BLP40-1024G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com