

BLVR-L05D-B1NS-N

BLVR-L05D-B1NS-N Information





Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BLVR-L05D-B1NS-N Specifications

Manufacturer All Sensors Corporation Category Sensors, Transducers Pressure Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP, Dual Ports, Same Side Series BLVR Pressure Type Differential Operating Pressure ±0.18 PSI (±1.25 kPa) Output Type Wheatstone Bridge Output Type 0 mV ~ 24 mV (3.3V) Accuracy ±2% Voltage - Supply 6V Port Size Barbless Features - Termination Style PC Pin Maximum Pressure +2%°C Package / Case 4-SIP, Dual Ports, Same Side Supplier Device Package 4-SIP, Dual Ports, Same Side		
CategorySensors, TransducersPackage4-SIP, Dual Ports, Same SidePackage4-SIP, Dual Ports, Same SideSeriesBLVRPressure TypeDifferentialOperating Pressure±0.18 PSI (±1.25 kPa)Output TypeWheatstone BridgeOutput Type0 mV ~ 24 mV (3.3V)Accuracy±2%Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Manufacturer Part Number	BLVR-L05D-B1NS-N
Pressure Sensors, TransducersPackage4-SIP, Dual Ports, Same SidePackageBLVRPressure TypeDifferentialOperating Pressure±0.18 PSI (±1.25 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 24 mV (3.3V)Accuracy±2%Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Manufacturer	All Sensors Corporation
Package4-SIP, Dual Ports, Same SideSeriesBLVRPressure TypeDifferentialOperating Pressure±0.18 PSI (±1.25 kPa)Output TypeWheatstone BridgeOutput Output0 mV ~ 24 mV (3.3V)Accuracy±2%Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Category	Sensors, Transducers
SeriesBLVRPressure TypeDifferentialOperating Pressure±0.18 PSI (±1.25 kPa)Output TypeWheatsone BridgeOutput Type0 mV ~ 24 mV (3.3V)Accuracy±2%Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4.SIP, Dual Ports, Same SideSupplier Device Package4.SIP		Pressure Sensors, Transducers
Pressure TypeDifferentialOperating Pressure±0.18 PSI (±1.25 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 24 mV (3.3V)Accuracy±2%Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Package	4-SIP, Dual Ports, Same Side
Ar±0.18 PSI (±1.25 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 24 mV (3.3V)Accuracy±2%Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Series	BLVR
Output TypeWheatstone BridgeOutput0 mV ~ 24 mV (3.3V)Accuracy±2%Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Pressure Type	Differential
Output 0 mV ~ 24 mV (3.3V) Accuracy ±2% Voltage - Supply 6V Port Size Male - 0.08" (2.04mm) Tube, Dual Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP, Dual Ports, Same Side	Operating Pressure	±0.18 PSI (±1.25 kPa)
Accuracy±2%Accuracy±2%Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Output Type	Wheatstone Bridge
Voltage - Supply6VPort SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Output	0 mV ~ 24 mV (3.3V)
Port SizeMale - 0.08" (2.04mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Accuracy	±2%
Port StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Voltage - Supply	6V
Features-Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Port Size	Male - 0.08" (2.04mm) Tube, Dual
Termination StylePC PinMaximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Port Style	Barbless
Maximum Pressure±7.23 PSI (±49.83 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Features	-
Operating Temperature-25°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Termination Style	PC Pin
Package / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Maximum Pressure	±7.23 PSI (±49.83 kPa)
Supplier Device Package 4-SIP	Operating Temperature	-25°C ~ 85°C
	Package / Case	4-SIP, Dual Ports, Same Side
Report errors?	Supplier Device Package	4-SIP
		Report errors?

E-mail: salesdept@heisener.com

BLVR-L05D-B1NS-N Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BLVR-L05D-B1NS-N Payment Methods



BLVR-L05D-B1NS-N Shipping Methods



If you have any question about BLVR-L05D-B1NS-N, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com