

BMVK6R3ADA470MF60G

BMVK6R3ADA470MF60G Information



For Reference Only

Part Number BMVK6R3ADA470MF60G

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 6.3V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BMVK6R3ADA470MF60G Specifications

Manufacturer Part NumberBMVK6R3ADA470MF60GManufacturerUnited Chemi-ConCategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAlchip?- MVK-BPCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzImpedance-
CategoryCapacitors Aluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAlchip?- MVK-BPCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency-
Aluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAlchip?- MVK-BPCapacitance $47μF$ Tolerance $±20%$ Voltage - Rated $6.3V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $1000 \text{ Hrs } @ 105 ^{\circ}\text{C}$ Operating Temperature $-40 ^{\circ}\text{C} \sim 105 ^{\circ}\text{C}$ PolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency $39mA @ 120Hz$ Ripple Current - High Frequency-
PackageRadial, Can - SMDSeriesAlchip?- MVK-BPCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency-
Series Alchip?- MVK-BP Capacitance $47\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $6.3V$ ESR (Equivalent Series Resistance) - Lifetime @ Temp. $1000 \text{ Hrs @ } 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency $39\text{mA @ } 120\text{Hz}$ Ripple Current - High Frequency $-$
Capacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency39mA @ 120HzRipple Current - High Frequency-
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 39mA @ 120Hz Ripple Current - High Frequency -
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency -
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 39mA @ 120Hz Ripple Current - High Frequency -
Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 39mA @ 120Hz Ripple Current - High Frequency -
Operating Temperature -40°C ~ 105°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 39mA @ 120Hz Ripple Current - High Frequency -
Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 39mA @ 120Hz Ripple Current - High Frequency -
Applications General Purpose Ripple Current - Low Frequency 39mA @ 120Hz Ripple Current - High Frequency -
Ripple Current - Low Frequency 39mA @ 120Hz Ripple Current - High Frequency -
Ripple Current - High Frequency -
Impedance -
Lead Spacing -
Size / Dimension 0.248" Dia (6.30mm)
Height - Seated (Max) 0.224" (5.70mm)
Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)
Mounting Type Surface Mount
Package / Case Radial, Can - SMD
Report errors?

BMVK6R3ADA470MF60G Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BMVK6R3ADA470MF60G Payment Methods



















BMVK6R3ADA470MF60G Shipping Methods













If you have any question about BMVK6R3ADA470MF60G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com