



### **BN074E0334K-- Information**

Heisener.com

**Part Number** BN074E0334K--**Manufacturer** AVX Corporation

**Category** Capacitors

Film Capacitors

**Description** CAP FILM 0.33UF 10% 100VDC RAD

Package Radial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **BN074E0334K-- Specifications**

Manufacturer Part Number         BN074E0334K           Manufacturer         AVX Corporation           Category         Capacitors           Package         Radial           Series         BN           Capacitance         0.33µF           Tolerance         ±10%           Voltage Rating - AC         63V           Voltage Rating - DC         100V           Dielectric Material         Polyester, Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -55°C ~ 125°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.398" L x 0.205" W (10.10mm x 5.20mm)           Height - Seated (Max)         0.402" (10.20mm)           Termination         PC Pins           Lead Spacing         0.295" (7.50mm)           Applications         High Pulse, DV/DT           Features         -	•	
Category         Capacitors           Film Capacitors           Package         Radial           Series         BN           Capacitance         0.33µF           Tolerance         ±10%           Voltage Rating - AC         63V           Voltage Rating - DC         100V           Dielectric Material         Polyester, Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -55°C ~ 125°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.398" L x 0.205" W (10.10mm x 5.20mm)           Height - Seated (Max)         0.402" (10.20mm)           Termination         PC Pins           Lead Spacing         0.295" (7.50mm)           Applications         High Pulse, DV/DT           Features         -	Manufacturer Part Number	BN074E0334K
Film Capacitors           Package         Radial           Series         BN           Capacitance         0.33μF           Tolerance         ±10%           Voltage Rating - AC         63V           Voltage Rating - DC         100V           Dielectric Material         Polyester, Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -55°C ~ 125°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.398" L x 0.205" W (10.10mm x 5.20mm)           Height - Seated (Max)         0.402" (10.20mm)           Termination         PC Pins           Lead Spacing         0.295" (7.50mm)           Applications         High Pulse, DV/DT           Features         -	Manufacturer	AVX Corporation
PackageRadialSeriesBNCapacitance0.33 µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.398" L x 0.205" W (10.10mm x 5.20mm)Height - Seated (Max)0.402" (10.20mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Category	Capacitors
Series         BN           Capacitance         0.33μF           Tolerance         ±10%           Voltage Rating - AC         63V           Voltage Rating - DC         100V           Dielectric Material         Polyester, Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -55°C ~ 125°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.398" L x 0.205" W (10.10mm x 5.20mm)           Height - Seated (Max)         0.402" (10.20mm)           Termination         PC Pins           Lead Spacing         0.295" (7.50mm)           Applications         High Pulse, DV/DT           Features         -		Film Capacitors
Capacitance $0.33\mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $63V$ Voltage Rating - DC $100V$ Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension $0.398^{\circ}L \times 0.205^{\circ}W (10.10mm \times 5.20mm)$ Height - Seated (Max) $0.402^{\circ}(10.20mm)$ TerminationPC PinsLead Spacing $0.295^{\circ}(7.50mm)$ ApplicationsHigh Pulse, DV/DTFeatures-	Package	Radial
Tolerance ±10%  Voltage Rating - AC  Voltage Rating - DC  100V  Dielectric Material  ESR (Equivalent Series Resistance)  Operating Temperature  -55°C ~ 125°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  0.398" L x 0.205" W (10.10mm x 5.20mm)  Height - Seated (Max)  Termination  PC Pins  Lead Spacing  0.295" (7.50mm)  Applications  High Pulse, DV/DT  Features  -	Series	BN
Voltage Rating - AC  Voltage Rating - DC  100V  Dielectric Material  ESR (Equivalent Series Resistance)  Operating Temperature  -55°C ~ 125°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  Height - Seated (Max)  Termination  PC Pins  Lead Spacing  O.295" (7.50mm)  High Pulse, DV/DT  Features  63V  63V  63V  63V  63V  63V  63V  100V  100V  100V  1010V  102°C  1000V  1	Capacitance	0.33μF
Voltage Rating - DC Dielectric Material Polyester, Metallized  ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.398" L x 0.205" W (10.10mm x 5.20mm) Height - Seated (Max) 0.402" (10.20mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications High Pulse, DV/DT Features -	Tolerance	±10%
Dielectric Material  ESR (Equivalent Series Resistance)  Operating Temperature  -55°C ~ 125°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  0.398" L x 0.205" W (10.10mm x 5.20mm)  Height - Seated (Max)  Termination  PC Pins  Lead Spacing  0.295" (7.50mm)  Applications  High Pulse, DV/DT  Features  -	Voltage Rating - AC	63V
ESR (Equivalent Series Resistance)  Operating Temperature  -55°C ~ 125°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  0.398" L x 0.205" W (10.10mm x 5.20mm)  Height - Seated (Max)  Termination  PC Pins  Lead Spacing  0.295" (7.50mm)  Applications  High Pulse, DV/DT  Features  -	Voltage Rating - DC	100V
Operating Temperature  -55°C ~ 125°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  0.398" L x 0.205" W (10.10mm x 5.20mm)  Height - Seated (Max)  0.402" (10.20mm)  Termination  PC Pins  Lead Spacing  0.295" (7.50mm)  Applications  High Pulse, DV/DT  Features  -	Dielectric Material	Polyester, Metallized
Mounting Type  Package / Case  Radial  Size / Dimension  Height - Seated (Max)  Termination  PC Pins  Lead Spacing  Applications  High Pulse, DV/DT  Features  Through Hole  Radial  0.398" L x 0.205" W (10.10mm x 5.20mm)  0.402" (10.20mm)  PC Pins  1.50mm)  1.50mm)  1.50mm)  1.50mm)  1.50mm)  1.50mm)	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.398" L x 0.205" W (10.10mm x 5.20mm)Height - Seated (Max)0.402" (10.20mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 125°C
Size / Dimension       0.398" L x 0.205" W (10.10mm x 5.20mm)         Height - Seated (Max)       0.402" (10.20mm)         Termination       PC Pins         Lead Spacing       0.295" (7.50mm)         Applications       High Pulse, DV/DT         Features       -	Mounting Type	Through Hole
Height - Seated (Max)  Termination  PC Pins  Lead Spacing  0.295" (7.50mm)  Applications  High Pulse, DV/DT  Features  -	Package / Case	Radial
Termination PC Pins  Lead Spacing 0.295" (7.50mm)  Applications High Pulse, DV/DT  Features -	Size / Dimension	0.398" L x 0.205" W (10.10mm x 5.20mm)
Lead Spacing0.295" (7.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Height - Seated (Max)	0.402" (10.20mm)
Applications High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

#### BN074E0334K-- Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **BN074E0334K-- Payment Methods**



















# **BN074E0334K-- Shipping Methods**













If you have any question about BN074E0334K--, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com