



BN104E0105K-- Information

Heisener.com

For Reference Only

Part Number BN104E0105K-Manufacturer AVX Corporation

Category Capacitors

Film Capacitors

Description CAP FILM 1UF 10% 100VDC RADIAL

Package Radial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BN104E0105K-- Specifications

Manufacturer Part Number BN104E0105K Manufacturer AVX Corporation Category Capacitors Film Capacitors Package Radial Series BN Capacitance 1μF Tolerance ±10% Voltage Rating - AC 63V Voltage Rating - DC 100V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) 0.535" (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features - Report errors?	•	
Category Capacitors Film Capacitors Package Radial Series BN Capacitance 1μF Tolerance ±10% Voltage Rating - AC 63V Voltage Rating - DC 100V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500° L x 0.205° W (12.70mm x 5.20mm) Height - Seated (Max) 0.535° (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Manufacturer Part Number	BN104E0105K
Film Capacitors Package Radial Series BN Capacitance 1μF Tolerance ±10% Voltage Rating - AC 63V Voltage Rating - DC 100V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) 0.535" (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Manufacturer	AVX Corporation
PackageRadialSeriesBNCapacitance1μFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.500" L x 0.205" W (12.70mm x 5.20mm)Height - Seated (Max)0.535" (13.60mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Pulse, DV/DTFeatures-	Category	Capacitors
Series BN Capacitance 1μF Tolerance ±10% Voltage Rating - AC 63V Voltage Rating - DC 100V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) 0.535" (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -		Film Capacitors
Capacitance $1\mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $63V$ Voltage Rating - DC $100V$ Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension 0.500° L x 0.205° W $(12.70 \text{mm x } 5.20 \text{mm})$ Height - Seated (Max) 0.535° (13.60 mm)TerminationPC PinsLead Spacing 0.394° (10.00 mm)ApplicationsHigh Pulse, DV/DTFeatures-	Package	Radial
Tolerance ±10% Voltage Rating - AC 63V Voltage Rating - DC 100V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) 0.535" (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Series	BN
Voltage Rating - AC Voltage Rating - DC 100V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features - 100V	Capacitance	1μF
Voltage Rating - DC Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature Operating Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Termination Lead Spacing Applications Features 100V Polyester, Metallized 100V 100V 100V 100V 100V 100V 100V 1000mm x 5.20mm 100	Tolerance	±10%
Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Voltage Rating - AC	63V
ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension O.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) Termination PC Pins Lead Spacing O.394" (10.00mm) Applications High Pulse, DV/DT Features	Voltage Rating - DC	100V
Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) 0.535" (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Dielectric Material	Polyester, Metallized
Mounting Type Package / Case Radial Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) 0.535" (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	ESR (Equivalent Series Resistance)	-
Package / Case Radial Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) 0.535" (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Operating Temperature	-55°C ~ 125°C
Size / Dimension 0.500" L x 0.205" W (12.70mm x 5.20mm) Height - Seated (Max) 0.535" (13.60mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Mounting Type	Through Hole
Height - Seated (Max) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Package / Case	Radial
Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications High Pulse, DV/DT Features -	Size / Dimension	0.500" L x 0.205" W (12.70mm x 5.20mm)
Lead Spacing0.394" (10.00mm)ApplicationsHigh Pulse, DV/DTFeatures-	Height - Seated (Max)	0.535" (13.60mm)
Applications High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	0.394" (10.00mm)
	Applications	High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

BN104E0105K-- Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BN104E0105K-- Payment Methods





















BN104E0105K-- Shipping Methods













If you have any question about BN104E0105K--, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com