

# **BP/FRN-R-15**

equest a Quote

### **BP/FRN-R-15 Information**

	Part Number	BP/FRN-R-15
	Manufacturer	Eaton
() Heisener.com	Category	Circuit Protection Electrical, Specialty Fuses FUSE TRON DUAL ELEMENT FUS Cartridge, Non-Standard For the pricing/inventory/lead time, please contac us Website: https://www.heisener.com
Count invoice case units	Description	FUSE TRON DUAL ELEMENT FUS
	Package	Cartridge, Non-Standard
		For the pricing/inventory/lead time, please contact
For Reference Only		

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **BP/FRN-R-15** Specifications

ManufacturerEatonCategoryCircuit ProtectionPackageCatridge, Non-StandardPackageCartridge, Non-StandardSeriesGartridge, Non-StandardFuser Or, PRNCartridgeCurren RatingCartridgeVoltage Rating - ACSoloVoltage Rating - DCSlovPactageSlovResponse TimeSlovApplicationsElectrical, IndustrialPactageCartogeApprovalsCE, CSA, ULOperating Peneture-Package/ CaseSlovACA CACA DCPackage / CaseCartridge, Non-StandardSize / DimensionStorige, Non-StandardSize / DimensionStorige, Non-StandardSize / DimensionStorige, Non-Standard			
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRNFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassKK5ApprovalsCE, CSA, ULOperating Temperature200kA AC, 20kA DCMounting TypeHolderPackage / CaseScons-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Manufacturer Part Number	BP/FRN-R-15	
EnergyElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRNFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature200kA AC, 20kA DCBreaking Capacity @ Rated VoltageCartridge, Non-StandardSize / Dimension0,560" Dia x 2.00" L (14.22mm x 50.80mm)	Manufacturer	Eaton	
PackageCartridge, Non-StandardSeriesFusetron? FRNFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Type-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Category	Circuit Protection	
SeriesFuseron? FRNFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeCurrent Rating15AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Package	Cartridge, Non-Standard	
Current Rating15ACurrent Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Series	Fusetron? FRN	
Voltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Fuse Type	Cartridge	
Voltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Current Rating	15A	
Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Voltage Rating - AC	250V	
ApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature200kA AC, 20kA DCBreaking Capacity @ Rated VoltageHolderPackage / CaseCartridge, Non-StandardBreaking Chape0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Voltage Rating - DC	125V	
Features-Features-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Response Time	Slow	
ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Applications	Electrical, Industrial	
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Features	-	
Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Class	RK5	
Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Approvals	CE, CSA, UL	
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Operating Temperature	-	
Package / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC	
Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Mounting Type	Holder	
	Package / Case	Cartridge, Non-Standard	
	Size / Dimension	0.560" Dia x 2.00" L (14.22mm x 50.80mm)	
Report errors?			Report errors?

#### **BP/FRN-R-15** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **BP/FRN-R-15** Payment Methods



## **BP/FRN-R-15** Shipping Methods



If you have any question about BP/FRN-R-15, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com