

BP/NON-100 Information

Heisener.com

Part Number BP/NON-100

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionBUSS ONE TIME FUSEPackageCartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BP/NON-100 Specifications

Manufacturer Part NumberBP/NON-100ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Manufacturer Part Number	BP/NON-100
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Manufacturer	Eaton
Package Cartridge, Non-Standard Series NON Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time - Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Category	Circuit Protection
SeriesNONFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time - Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Series	NON
Voltage Rating - AC Voltage Rating - DC 125V Response Time - Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 250V 1050 1050 1050 1060 1070	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Holder Package / Case Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Current Rating	100A
Response Time Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - Clectrical, Industrial - CE, CSA, UL - CE, CSA	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Voltage Rating - DC	125V
Features - Class H Approvals CE, CSA, UL Operating Temperature - IokA Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Response Time	-
Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Class	Н
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Mounting Type	Holder
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.060" Dia x 5.88" W (26.92mm x 149.35mm)
±		Report errors?

BP/NON-100 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BP/NON-100 Payment Methods



















BP/NON-100 Shipping Methods













If you have any question about BP/NON-100, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com