

BP/NON-40

Request a Quote

BP/NON-40 Information

Heisener.com	Part Number	BP/NON-40
	Manufacturer	Eaton
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	BUSS ONE TIME FUSE
	Package	Cartridge, Non-Standard
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BP/NON-40 Specifications

Manufacturer Part NumberBP/NON-40ManufacturerEatonCategoryCircuit ProtectionBectrical, Specialty FusesPackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC25VResponse Time-ApplicationsElectrical, IndustrialParameterSApprovalsCS, AULOperating Temperature-ApprovalsSokAMounting TypeHolderPackage / CaseSokAStory CaseCartridge, Non-StandardPackage / CaseSokAPackage / CaseCartridge, Non-StandardPackage / CaseCartridge, Non-StandardPackage / CaseSokaPackage / CaseCartridge, Non-StandardPackage / Ca			
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardPackageNONSeriesNONFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFatures-ClassS5ApprovalsCE, CSA, ULOperating Temperature50kAMounting TypeSide MainePackage / CaseSider MaineSider / DimensionSider StandardSider / DimensionSider Stan	Manufacturer Part Number	BP/NON-40	
Interform Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Manufacturer	Eaton	
PackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5Operating Temperature50KAOperating Capacity @ Rated Voltage50KAMounting TypeFolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Category	Circuit Protection	
SeriesNONFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeFuse Type40AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsElectroActunctOperating Temperature-Breaking Capacity @ Rated Voltage50KAMounting TypeGalderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Package	Cartridge, Non-Standard	
Current Rating40AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810"Dia x 3.00"L (20.57mm x 76.20mm)	Series	NON	
Voltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature50kAHounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Fuse Type	Cartridge	
Voltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Current Rating	40A	
Response Time-Response Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Voltage Rating - AC	250V	
ApplicationsElectrical, IndustrialApplications-Features-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Voltage Rating - DC	125V	
Features-Features-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Response Time	-	
ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Applications	Electrical, Industrial	
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Features	-	
Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Class	K5	
Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Approvals	CE, CSA, UL	
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Operating Temperature	-	
Package / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Breaking Capacity @ Rated Voltage	50kA	
Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Mounting Type	Holder	
	Package / Case	Cartridge, Non-Standard	
	Size / Dimension	0.810" Dia x 3.00" L (20.57mm x 76.20mm)	
Report errors?		Report error	ors?

BP/NON-40 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BP/NON-40 Payment Methods



BP/NON-40 Shipping Methods



If you have any question about BP/NON-40, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com