

BP5034D24 Information



For Reference Only

Part Number BP5034D24

Manufacturer Rohm Semiconductor

Category Power Supplies - Board Mount

AC DC Converters

Description IC CONV AC/DC 24V 50MA SIP10

Package 10-DIP Module, 9 Leads

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BP5034D24 Specifications

Manufacturer Part NumberBP5034D24ManufacturerRohm SemiconductorCategoryPower Supplies - Board MountAC DC ConvertersPackage10-DIP Module, 9 LeadsSeriesBP5034TypeEnclosedNumber of Outputs1Voltage - Input80 ~ 138 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)50mAPower (Watts)1W	
Category Power Supplies - Board Mount AC DC Converters Package 10-DIP Module, 9 Leads Series BP5034 Type Enclosed Number of Outputs 1 Voltage - Input 80 ~ 138 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Package 10-DIP Module, 9 Leads Series BP5034 Type Enclosed Number of Outputs 1 Voltage - Input 80 ~ 138 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Package 10-DIP Module, 9 Leads Series BP5034 Type Enclosed Number of Outputs 1 Voltage - Input 80 ~ 138 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Series BP5034 Type Enclosed Number of Outputs 1 Voltage - Input 80 ~ 138 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Type Enclosed Number of Outputs 1 Voltage - Input 80 ~ 138 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Number of Outputs 1 Voltage - Input 80 ~ 138 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Voltage - Input 80 ~ 138 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 Current - Output (Max) 80 ~ 138 VAC 24V Curent - Output 2 - Curent - Output 3	
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 50mA	
Voltage - Output 4 - Current - Output (Max) 50mA	
Current - Output (Max) 50mA	
• , ,	
Power (Watts) 1W	
Applications ITE (Commercial)	
Features -	
Operating Temperature $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$ (With Derating)	
Efficiency 72%	
Mounting Type Through Hole	
Package / Case 10-DIP Module, 9 Leads	
Size / Dimension 1.11" L x 0.39" W x 0.62" H (28.2mm x 10.0mm x 15.7mm)	
Report en	ors?

BP5034D24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BP5034D24 Payment Methods


































If you have any question about BP5034D24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com