

BP5081A15 Information



For Reference Only

Part Number BP5081A15

Manufacturer Rohm Semiconductor

Category Power Supplies - Board Mount

AC DC Converters

Description IC AC/DC CONVERTER DUAL SIP14

Package 14-SIP Module, 8 Leads

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BP5081A15 Specifications

Manufacturer Part Number BP5081A15 Manufacturer Rohm Semiconductor Category Power Supplies - Board Mount AC DC Converters Package 14-SIP Module, 8 Leads Series BP5081 Type Enclosed Number of Outputs 2 Voltage - Input 80 ~ 120 VAC Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 15.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm) Report errors?		
Category Power Supplies - Board Mount AC DC Converters Package 14-SIP Module, 8 Leads Series BP5081 Type Enclosed Number of Outputs 2 Voltage - Input 80 ~ 120 VAC Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Manufacturer Part Number	BP5081A15
Package 14-SIP Module, 8 Leads Series BP5081 Type Enclosed Number of Outputs 2 Voltage - Input 80 ~ 120 VAC Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Manufacturer	Rohm Semiconductor
Package 14-SIP Module, 8 Leads Series BP5081 Type Enclosed Number of Outputs 2 Voltage - Input 80 ~ 120 VAC Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Category	Power Supplies - Board Mount
Series BP5081 Type Enclosed Number of Outputs 2 Voltage - Input 80 ~ 120 VAC Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)		AC DC Converters
Type Enclosed Number of Outputs 2 Voltage - Input 80 ~ 120 VAC Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Package	14-SIP Module, 8 Leads
Number of Outputs 2 Voltage - Input 80 ~ 120 VAC Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Series	BP5081
Voltage - Input 80 ~ 120 VAC Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Туре	Enclosed
Voltage - Output 1 15V Voltage - Output 2 5V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Number of Outputs	2
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features - Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension 5V Solve (Watts) Size / Dimension Solve (Watts) Size / Dimension Solve (Watts) Size / Output 2 Solve (Watts) Size / Output 3 Size / Output 4 Size / Output 4 Size / Output 4 Size / Output 3 Size / Output 3 Size / Output 4 Size /	Voltage - Input	80 ~ 120 VAC
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features -25°C ~ 80°C (With Derating) Efficiency Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension - S0mA, 350mA - With Derating (With Derating)	Voltage - Output 2	5V
Current - Output (Max) 80mA, 350mA Power (Watts) 3W Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 3W ITE (Commercial) - Norman Size / With Derating Size / With Derat	Voltage - Output 4	-
Applications ITE (Commercial) Features - Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Current - Output (Max)	80mA, 350mA
Features - Coperating Temperature -25°C ~ 80°C (With Derating) Efficiency - Company Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Power (Watts)	3W
Operating Temperature -25°C ~ 80°C (With Derating) Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Applications	ITE (Commercial)
Efficiency - Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Features	-
Mounting Type Through Hole Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Operating Temperature	-25°C ~ 80°C (With Derating)
Package / Case 14-SIP Module, 8 Leads Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Efficiency	-
Size / Dimension 1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)	Mounting Type	Through Hole
	Package / Case	14-SIP Module, 8 Leads
Report errors?	Size / Dimension	1.59" L x 0.49" W x 0.85" H (40.5mm x 12.4mm x 21.5mm)
		Report errors?

BP5081A15 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BP5081A15 Payment Methods



















BP5081A15 Shipping Methods













If you have any question about BP5081A15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com