

Heisener.com

BS016010BE50036BJ1

BS016010BE50036BJ1 Information

Part Number BS016010BE50036BJ1
Manufacturer Vishay Beyschlag

Category Capacitors

Ceramic Capacitors

Description CAP CER 50PF 5KV AXIAL **Package** Axial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BS016010BE50036BJ1 Specifications

Manufacturer Part Number BS016010BE50036BJ1 Manufacturer Vishay Beyschlag Category Capacitors Package Axial, Can - Screw Terminals Series - Capacitance 50pF Tolerance ±10% Voltage - Rated 5000V (5kV) Temperature Coefficient - Operating Temperature - Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package Axial, Can - Screw Terminals Series - Capacitance 50pF Tolerance ±10% Voltage - Rated 5000V (5kV) Temperature Coefficient - Operating Temperature - Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	BS016010BE50036BJ1
Package Axial, Can - Screw Terminals Series - Capacitance 50pF Tolerance ±10% Voltage - Rated 5000V (5kV) Temperature Coefficient - Operating Temperature - Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	Vishay Beyschlag
Package Axial, Can - Screw Terminals Series - Capacitance 50pF Tolerance ±10% Voltage - Rated 5000V (5kV) Temperature Coefficient - Operating Temperature - Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 50pF Tolerance ±10% Voltage - Rated 5000V (5kV) Temperature Coefficient - Operating Temperature - Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 50pF Tolerance ±10% Voltage - Rated 5000V (5kV) Temperature Coefficient - Operating Temperature - Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial, Can - Screw Terminals
Tolerance ±10% Voltage - Rated 5000V (5kV) Temperature Coefficient - Operating Temperature - Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Series	-
Voltage - Rated5000V (5kV)Temperature Coefficient-Operating Temperature-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeChassis MountPackage / CaseAxial, Can - Screw TerminalsSize / Dimension0.630" Dia x 0.906" L (16.00mm x 23.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	50pF
Temperature Coefficient Operating Temperature Features Features Features Features Features Features Features Features Features Failure Rate Feature Rate Feature Rate Foliations Foliations Foliations Foliations Failure Rate Foliations Foliatio	Tolerance	±10%
Operating Temperature - Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Voltage - Rated	5000V (5kV)
Features Ratings - Applications General Purpose Failure Rate Failure Rate Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Temperature Coefficient	-
Ratings - General Purpose Failure Rate - Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Chassis	Operating Temperature	-
Applications General Purpose Failure Rate - Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	-
Failure Rate - Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Chassis Mount	Ratings	-
Mounting Type Chassis Mount Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style	Applications	General Purpose
Package / Case Axial, Can - Screw Terminals Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.630" Dia x 0.906" L (16.00mm x 23.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Chassis Mount
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial, Can - Screw Terminals
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.630" Dia x 0.906" L (16.00mm x 23.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

BS016010BE50036BJ1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BS016010BE50036BJ1 Payment Methods



















BS016010BE50036BJ1 Shipping Methods













If you have any question about BS016010BE50036BJ1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com