

BS2660-7R Information



For Reference Only

Part Number BS2660-7R

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERT DUAL 24V 2A

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BS2660-7R Specifications

Manufacturer Part Number BS 2660-7R Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher S Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature 2-5°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher S Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Manufacturer Part Number	BS2660-7R	
Package Module Series Melcher S Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Manufacturer	Bel Power Solutions	
Package Module Series Melcher S Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series Melcher S Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)		DC DC Converters	
Type Isolated Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Package	Module	
Voltage - Input (Min) 14V Voltage - Input (Max) 70V Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Series	Melcher S	
Voltage - Input (Max) 70V Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Type	Isolated	
Number of Outputs 2 Voltage - Output 1 24V Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A, 2A Power (Watts) 100W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Input (Min)	14V	
Voltage - Output 1 Voltage - Output 2 24V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Railway Operating Temperature Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 24V 24V 24V Current - Output (Max) - 100W Applications ITE (Commercial), Railway Chassis Mount 100W	Voltage - Input (Max)	70V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension 24V 24V 24V 24V 24V - 25°C ~ 71°C 24V - Current - Output (Max) - 2A, 2A - 100W ITE (Commercial), Railway - 25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Number of Outputs	2	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension	Voltage - Output 1	24V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension -25°C ~ 71°W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Voltage - Output 2	24V	
Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2A, 2A 100W Commercial), Railway -25°C ~ 71°C Chassis Mount 100W	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 100W Railway -25°C ~ 71°C Chassis Mount 100W 10	Voltage - Output 4	-	
Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Current - Output (Max)	2A, 2A	
Operating Temperature -25°C ~ 71°C Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Power (Watts)	100W	
Efficiency 82% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Applications	ITE (Commercial), Railway	
Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Operating Temperature	-25°C ~ 71°C	
Package / Case Module Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Efficiency	82%	
Size / Dimension 6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	Mounting Type	Chassis Mount	
	Package / Case	Module	
Report errors?	Size / Dimension	6.73" L x 4.37" W x 2.06" H (171.0mm x 111.0mm x 52.2mm)	
K.			Report errors?

BS2660-7R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BS2660-7R Payment Methods





















BS2660-7R Shipping Methods













If you have any question about BS2660-7R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com