

BSW-113-24-S-D

BSW-113-24-S-D Information

Heisener.com	Manufacturer Category	BSW-113-24-S-D Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets BOTTOM MOUNT STRIPS	
	Description	BOTTOM MOUNT STRIPS	
	Package	-	- 国際常務部
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BSW-113-24-S-D Specifications

Manufacturer Part NumberBSW-113-24-S-DManufacturerSamtec Inc.CategoryConnectors, InterconnectsPackage-SeriesBSWConnector TypeReceptacles, Female SocketsContact TypeFemale SocketStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldNundition ColorBack		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypeQuin (0.76µm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Manufacturer Part Number	BSW-113-24-S-D
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypeQuin (0.76µm)Contact Finish - MatingGoldInsulation ColorBlack	Manufacturer	Samtec Inc.
Package-SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypeQuidContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Category	Connectors, Interconnects
SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypeQui AllContact Finish - MatingGoldInsulation ColorBlack		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeO.100" (2.54mm)Fastening TypeSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlack	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIontact Finish Thickness - MatingBlack	Series	BSW
StyleBoard to BoardStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Connector Type	Receptacle, Breakaway
Number of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Number of Positions	26
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough Hole, Bottom MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlack	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlack	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlack	Mounting Type	Through Hole, Bottom Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlack	Termination	Solder
Contact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlack	Fastening Type	Push-Pull
Insulation Color Black	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	30µin (0.76µm)
	Insulation Color	Black
Insulation Height 0.350" (8.89mm)	Insulation Height	0.350" (8.89mm)
Contact Length - Post 0.165" (4.19mm)	Contact Length - Post	0.165" (4.19mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

BSW-113-24-S-D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BSW-113-24-S-D Payment Methods



If you have any question about BSW-113-24-S-D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com