

# BSW-126-24-L-D

### **BSW-126-24-L-D Information**

Part Number Manufacturer	BSW-126-24-L-D Samtec Inc.	
Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
Description	BOTTOM MOUNT STRIPS	
Package	-	国際優勝に
	For the pricing/inventory/lead time, please contact	
For Reference Only	Website: https://www.heisener.com	Request a Quote
	Manufacturer Category Description	Manufacturer Samtec Inc.   Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets   Description BOTTOM MOUNT STRIPS   Package -   For the pricing/inventory/lead time, please contact us

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **BSW-126-24-L-D Specifications**

Manufacturer Part NumberBSW-126-24-L-DManufacturerSantec Inc.CategoryConnectors, InterconnectsPackage-Package-SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountFerminationSolder		
CategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of PositionsS2Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - MatingDinou" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Manufacturer Part Number	BSW-126-24-L-D
Hectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions52Number of Positions Loaded0.100°(2.54mm)Number of Rows2Row Spacing - Mating0.100°(2.54mm)Mounting TypeThrough Hole, Bottom MountSolderSolder	Manufacturer	Samtec Inc.
Package-Package-SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions52Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Category	Connectors, Interconnects
SeriesBSWConnector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions52Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, BreakawayContact TypeFemale SocketStyleBoard to BoardNumber of Positions52Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions52Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Series	BSW
StyleBoard to BoardNumber of Positions52Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Connector Type	Receptacle, Breakaway
Number of Positions52Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Number of Positions	52
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Bottom MountTerminationSolder	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough Hole, Bottom MountTerminationSolder	Number of Rows	2
Termination Solder	Row Spacing - Mating	0.100" (2.54mm)
	Mounting Type	Through Hole, Bottom Mount
Fastening Type Push-Pull	Termination	Solder
	Fastening Type	Push-Pull
Contact Finish - Mating Gold	Contact Finish - Mating	Gold
Contact Finish Thickness - Mating 10µin (0.25µm)	Contact Finish Thickness - Mating	10µin (0.25µm)
Insulation Color Black	Insulation Color	Black
Insulation Height 0.350" (8.89mm)	Insulation Height	0.350" (8.89mm)
Contact Length - Post 0.165" (4.19mm)	Contact Length - Post	0.165" (4.19mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	$-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### **BSW-126-24-L-D Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **BSW-126-24-L-D Payment Methods**



If you have any question about BSW-126-24-L-D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com