

BT24-2A66 Information



For Reference Only

Part Number BT24-2A66

Manufacturer Standex-Meder Electronics

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST 500MA 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BT24-2A66 Specifications

| Manufacturer Part NumberBT24-2A66ManufacturerStandex-Meder ElectronicsCategoryRelaysPackage-SeriesBTRelay TypeReedCoil TypeNon LatchingCoil Current1.17mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 200VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.5 VDCOperate Time0.5msRelease Time0.1msFeatures-Mounting TypeThrough HoleTermination StylePC Pin | | |
|--|--------------------------|-----------------------------|
| CategoryRelaysPackage-SeriesBTRelay TypeReedCoil TypeNon LatchingCoil Current1.17mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.5 VDCOperate Time0.5msRelease Time0.1msFeatures-Mounting TypeThrough HoleTermination StylePC Pin | Manufacturer Part Number | BT24-2A66 |
| Package-SeriesBTRelay TypeReedCoil TypeNon LatchingCoil Current1.17mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.5 VDCOperate Time0.5msRelease Time0.1msFeatures-Mounting TypeThrough HoleTermination StylePC Pin | Manufacturer | Standex-Meder Electronics |
| Package - Series BT Relay Type Reed Coil Type Non Latching Coil Current 1.17mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 3.5 VDC Operate Time 0.5ms Release Time 0.1ms Features - Mounting Type Through Hole Termination Style PC Pin | Category | Relays |
| SeriesBTRelay TypeReedCoil TypeNon LatchingCoil Current1.17mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.5 VDCOperate Time0.5msRelease Time0.1msFeatures-Mounting TypeThrough HoleTermination StylePC Pin | | Signal Relays, Up to 2 Amps |
| Relay TypeReedCoil TypeNon LatchingCoil Current1.17mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.5 VDCOperate Time0.5msRelease Time0.1msFeatures-Mounting TypeThrough HoleTermination StylePC Pin | Package | - |
| Coil TypeNon LatchingCoil Current1.17mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)3.5 VDCOperate Time0.5msRelease Time0.1msFeatures-Mounting TypeThrough HoleTermination StylePC Pin | Series | BT |
| Coil Current Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 3.5 VDC Operate Time 0.5ms Release Time 0.1ms Features - Mounting Type Through Hole Termination Style 1.17mA 1.17mA 24VDC 0DPST (2 Form A) 500mA 500mA 500mA 500mA 600mA 6 | Relay Type | Reed |
| Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 3.5 VDC Operate Time 0.5ms Release Time 0.1ms Features - Mounting Type Through Hole Termination Style PC Pin | Coil Type | Non Latching |
| Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 3.5 VDC Operate Time 0.5ms Release Time 0.1ms Features - Mounting Type Through Hole Termination Style PC Pin | Coil Current | 1.17mA |
| Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 3.5 VDC Operate Time 0.5ms Release Time 0.1ms Features - Mounting Type Through Hole Termination Style | Coil Voltage | 24VDC |
| Switching Voltage Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time O.5ms Release Time O.1ms Features Mounting Type Through Hole Termination Style 200VAC, 200VDC - Max 18 VDC 0.5ms 0.5ms Through Hole PC Pin | Contact Form | DPST (2 Form A) |
| Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time O.5ms Release Time O.1ms Features Mounting Type Through Hole Termination Style 18 VDC 0.5ms 0.5ms Through Hole PC Pin | Contact Rating (Current) | 500mA |
| Turn Off Voltage (Min) Operate Time 0.5ms Release Time 0.1ms Features Mounting Type Through Hole Termination Style 3.5 VDC 0.5ms Through Hole | Switching Voltage | 200VAC, 200VDC - Max |
| Operate Time 0.5ms Release Time 0.1ms Features - Mounting Type Through Hole Termination Style PC Pin | Turn On Voltage (Max) | 18 VDC |
| Release Time 0.1ms Features - Mounting Type Through Hole Termination Style PC Pin | Turn Off Voltage (Min) | 3.5 VDC |
| Features - Mounting Type Through Hole Termination Style PC Pin | Operate Time | 0.5ms |
| Mounting Type Through Hole Termination Style PC Pin | Release Time | 0.1ms |
| Termination Style PC Pin | Features | - |
| · | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin |
| | | Report errors? |

BT24-2A66 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BT24-2A66 Payment Methods





















BT24-2A66 Shipping Methods













If you have any question about BT24-2A66, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com