

### BV020-5432.0 Information



For Reference Only

Part Number BV020-5432.0

Manufacturer Pulse Electronics Power

**Category** Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 0.35VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **BV020-5432.0 Specifications**

Manufacturer Part NumberBV020-5432.0ManufacturerPulse Electronics PowerCategoryTransformersPower TransformersPower TransformersPackage-Series-TypeLaminated CoreVoltage - Primary230VVoltage - Secondary (Full Load)Parallel 15V, Series 30VCurrent - Output (Max)Parallel 24mA, Series 12mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max0.35 VAMounting TypeThrough HoleTermination StylePC Pin		
CategoryTransformersPackage-Series-TypeLaminated CoreVoltage - Primary230VVoltage - Secondary (Full Load)Parallel 15V, Series 30VCurrent - Output (Max)Parallel 24mA, Series 12mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max0.35 VAMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	BV020-5432.0
Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) Parallel 15V, Series 30V Current - Output (Max) Parallel 24mA, Series 12mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 0.35 VA Mounting Type Through Hole Termination Style Power Transformers  - Rower Tr	Manufacturer	Pulse Electronics Power
Package - Series - Caminated Core Laminated Core Voltage - Primary 230V Parallel 15V, Series 30V Parallel 15V, Series 30V Parallel 24mA, Series 12mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 0.35 VA Mounting Type Through Hole Termination Style PC Pin	Category	Transformers
Series Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) Parallel 15V, Series 30V Current - Output (Max) Parallel 24mA, Series 12mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 0.35 VA Mounting Type Through Hole Termination Style PC Pin		Power Transformers
Type Laminated Core  Voltage - Primary 230V  Voltage - Secondary (Full Load) Parallel 15V, Series 30V  Current - Output (Max) Parallel 24mA, Series 12mA  Primary Winding(s) Single  Secondary Winding(s) Dual  Center Tap No  Power - Max 0.35 VA  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Voltage - Primary  230V  Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 24mA, Series 12mA  Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  230V  Parallel 15V, Series 30V  Parallel 24mA, Series 12mA  Parallel 24mA, Series 12mA  No  Dual  Center Tap  No  Power - Max  D.35 VA  Through Hole	Series	-
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 24mA, Series 12mA  Primary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Parallel 15V, Series 30V  Parallel 24mA, Series 12mA  Single  No  Dual  O.35 VA  Through Hole  PC Pin	Туре	Laminated Core
Current - Output (Max)Parallel 24mA, Series 12mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max0.35 VAMounting TypeThrough HoleTermination StylePC Pin	Voltage - Primary	230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 0.35 VA Mounting Type Through Hole Termination Style Primary Winding(s) Single Out Dual Powal Pow	Voltage - Secondary (Full Load)	Parallel 15V, Series 30V
Secondary Winding(s)DualCenter TapNoPower - Max0.35 VAMounting TypeThrough HoleTermination StylePC Pin	Current - Output (Max)	Parallel 24mA, Series 12mA
Center TapNoPower - Max0.35 VAMounting TypeThrough HoleTermination StylePC Pin	Primary Winding(s)	Single
Power - Max 0.35 VA  Mounting Type Through Hole  Termination Style PC Pin	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin	Center Tap	No
Termination Style PC Pin	Power - Max	0.35 VA
	Mounting Type	Through Hole
	Termination Style	PC Pin
Size / Dimension 22.00mm L x 23.00mm W	Size / Dimension	22.00mm L x 23.00mm W
Height - Seated (Max) 15.00mm	Height - Seated (Max)	15.00mm
Voltage - Isolation -	Voltage - Isolation	-
Weight 0.077 lb (34.93g)	Weight	0.077 lb (34.93g)
Report errors?		Report errors?

### BV020-5432.0 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **BV020-5432.0 Payment Methods**





















### **BV020-5432.0** Shipping Methods













If you have any question about BV020-5432.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com