

BV030-6866.0 Information

Heisener.com

Part Number BV030-6866.0

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 2VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BV030-6866.0 Specifications

Manufacturer Part NumberBV030-6866.0ManufacturerPulse Electronics PowerCategoryTransformersPackage-Series-TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6V, Series 12VCurrent - Output (Max)Parallel 332mA, Series 166mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension53.00mm L x 44.00mm WVoltage - Isolation-Weight0.133 lb (60.33g)		
Category Transformers Package - Series - Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 332mA, Series 166mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer Part Number	BV030-6866.0
Package - Series - Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 332mA, Series 166mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer	Pulse Electronics Power
Package - Series - Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 332mA, Series 166mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Category	Transformers
Series - Caminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 332mA, Series 166mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 60.33g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 332mA, Series 166mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 332mA, Series 166mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Fasted (Max) 17.00mm Voltage - Isolation Voltage - Isolation Voltage - Isolation O.133 lb (60.33g)	Series	-
Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 332mA, Series 166mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Voltage - Isolation 0.133 lb (60.33g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Voltage - Isolation Voltage - Isolation Vinding Secondary Winding(s) Dual Powal No Powal No Powal No Powar No No Powar No No Powar No	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) Voltage - Isolation - Weight 0.133 lb (60.33g)	Voltage - Secondary (Full Load)	Parallel 6V, Series 12V
Secondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension53.00mm L x 44.00mm WHeight - Seated (Max)17.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Current - Output (Max)	Parallel 332mA, Series 166mA
Center TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension53.00mm L x 44.00mm WHeight - Seated (Max)17.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Primary Winding(s)	Dual
Power - Max 2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Center Tap	No
Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Power - Max	2 VA
Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 17.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 17.00mm - 0.133 lb (60.33g)	Termination Style	PC Pin
Voltage - Isolation - Weight 0.133 lb (60.33g)	Size / Dimension	53.00mm L x 44.00mm W
Weight 0.133 lb (60.33g)	Height - Seated (Max)	17.00mm
	Voltage - Isolation	-
Report errors?	Weight	0.133 lb (60.33g)
		Report errors?

BV030-6866.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BV030-6866.0 Payment Methods



















BV030-6866.0 Shipping Methods













If you have any question about BV030-6866.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com