

# BV030-7154.0 Information

Heisener.com

Part Number BV030-7154.0

Manufacturer Pulse Electronics Power

Category Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 1.5VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **BV030-7154.0 Specifications**

Manufacturer Part Number         BV030-7154.0           Manufacturer         Pulse Electronics Power           Category         Transformers           Package         -           Series         -           Type         Laminated Core           Voltage - Primary         115V           Voltage - Secondary (Full Load)         24V           Current - Output (Max)         62mA           Primary Winding(s)         Single           Secondary Winding(s)         Single           Center Tap         No           Power - Max         1.5 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         32.50mm L x 27.50mm W           Height - Seated (Max)         24.00mm           Voltage - Isolation         -           Weight         0.133 lb (60.33g)		
CategoryTransformersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)24VCurrent - Output (Max)62mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max1.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)24.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Manufacturer Part Number	BV030-7154.0
Package         -           Series         -           Type         Laminated Core           Voltage - Primary         115V           Voltage - Secondary (Full Load)         24V           Current - Output (Max)         62mA           Primary Winding(s)         Single           Secondary Winding(s)         Single           Center Tap         No           Power - Max         1.5 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         32.50mm L x 27.50mm W           Height - Seated (Max)         24.00mm           Voltage - Isolation         -           Weight         0.133 lb (60.33g)	Manufacturer	Pulse Electronics Power
Package         -           Series         -           Type         Laminated Core           Voltage - Primary         115 V           Voltage - Secondary (Full Load)         24 V           Current - Output (Max)         62mA           Primary Winding(s)         Single           Secondary Winding(s)         Single           Center Tap         No           Power - Max         1.5 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         32.50mm L x 27.50mm W           Height - Seated (Max)         24.00mm           Voltage - Isolation         -           Weight         0.133 lb (60.33g)	Category	Transformers
Series         -           Type         Laminated Core           Voltage - Primary         115 V           Voltage - Secondary (Full Load)         24 V           Current - Output (Max)         62mA           Primary Winding(s)         Single           Secondary Winding(s)         Single           Center Tap         No           Power - Max         1.5 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         32.50mm L x 27.50mm W           Height - Seated (Max)         24.00mm           Voltage - Isolation         -           Weight         0.133 lb (60.33g)		Power Transformers
Type Laminated Core  Voltage - Primary 115V  Voltage - Secondary (Full Load) 24V  Current - Output (Max) 62mA  Primary Winding(s) Single  Secondary Winding(s) Single  Center Tap No Power - Max 1.5 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 32.50mm L x 27.50mm W  Height - Seated (Max) 24.00mm  Voltage - Isolation -  Weight 0.133 lb (60.33g)	Package	-
Voltage - Primary       115V         Voltage - Secondary (Full Load)       24V         Current - Output (Max)       62mA         Primary Winding(s)       Single         Secondary Winding(s)       Single         Center Tap       No         Power - Max       1.5 VA         Mounting Type       Through Hole         Termination Style       PC Pin         Size / Dimension       32.50mm L x 27.50mm W         Height - Seated (Max)       24.00mm         Voltage - Isolation       -         Weight       0.133 lb (60.33g)	Series	-
Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  1.5 VA  Mounting Type  Through Hole  Termination Style  Size / Dimension  Yoltage - Isolation  Voltage - Isolation  Voltage - Isolation  24V  24V  26  26  27  87  87  87  88  89  89  89  80  80  80  80  80  80	Туре	Laminated Core
Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  1.5 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  32.50mm L x 27.50mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Weight  62mA  62m  62m	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 1.5 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Height - Seated (Max) Voltage - Isolation Veight Single Single No PO No 1.5 VA Through Hole PC Pin 32.50mm L x 27.50mm W 24.00mm - 0.133 lb (60.33g)	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapNoPower - Max1.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)24.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Current - Output (Max)	62mA
Center Tap No  Power - Max 1.5 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 32.50mm L x 27.50mm W  Height - Seated (Max) 24.00mm  Voltage - Isolation -  Weight 0.133 lb (60.33g)	Primary Winding(s)	Single
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  32.50mm L x 27.50mm W  Height - Seated (Max)  Voltage - Isolation  -  Weight  1.5 VA  1.5 VA  1.5 VA  1.5 VA  1.6 VA  1.7 VA  1.7 VA  1.7 VA  1.8 VA  1.9 VA  1	Secondary Winding(s)	Single
Mounting Type Through Hole PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Center Tap	No
Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm  Voltage - Isolation - Weight 0.133 lb (60.33g)	Power - Max	1.5 VA
Size / Dimension 32.50mm L x 27.50mm W  Height - Seated (Max) 24.00mm  Voltage - Isolation -  Weight 0.133 lb (60.33g)	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  Weight  24.00mm  -  0.133 lb (60.33g)	Termination Style	PC Pin
Voltage - Isolation - Weight 0.133 lb (60.33g)	Size / Dimension	32.50mm L x 27.50mm W
Weight 0.133 lb (60.33g)	Height - Seated (Max)	24.00mm
	Voltage - Isolation	-
Report errors?	Weight	0.133 lb (60.33g)
		Report errors?

### BV030-7154.0 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **BV030-7154.0 Payment Methods**



















### **BV030-7154.0** Shipping Methods













If you have any question about BV030-7154.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com