

BV030-7186.0 Information

Heisener.com

Part Number BV030-7186.0

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 0.5VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BV030-7186.0 Specifications

Manufacturer Part Number BV030-7186.0 Manufacturer Pulse Electronics Power Category Transformers Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 12V Current - Output (Max) 42mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)		
Category Transformers Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 12V Current - Output (Max) 42mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer Part Number	BV030-7186.0
Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 12V Current - Output (Max) 42mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer	Pulse Electronics Power
Package - Series - Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 12 V Current - Output (Max) 42mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Category	Transformers
Series - Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 12 V Current - Output (Max) 42mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 12V Current - Output (Max) 42mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) 12V Current - Output (Max) 42mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Voltage for a secondary (Full Load) 115V 12V 12V 12V 12V 12P 12V 12P 12P 12P 12P 12P 12P 13P 13P 14P 15P 15P 15P 15P 15P 15P 15P 15P 15P 15	Series	-
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Veight 12V 42mA 42mA 42mA 42mA 42mA 42mA 42mA 42mA 42mA 5ingle No Pople No 15.00m 15.00mm Voltage - Isolation - 0.133 lb (60.33g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Veight 42mA 42ma	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Height - Seated (Max) Voltage - Isolation Veight Single Single No PO No No 1.5 VA Through Hole PC Pin 32.50mm L x 27.50mm W 15.00mm - 0.133 lb (60.33g)	Voltage - Secondary (Full Load)	12V
Secondary Winding(s)SingleCenter TapNoPower - Max0.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)15.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Current - Output (Max)	42mA
Center Tap No Power - Max 0.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Secondary Winding(s)	Single
Mounting Type Through Hole PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Center Tap	No
Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Power - Max	0.5 VA
Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 15.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 15.00mm - 0.133 lb (60.33g)	Termination Style	PC Pin
Voltage - Isolation - Weight 0.133 lb (60.33g)	Size / Dimension	32.50mm L x 27.50mm W
Weight 0.133 lb (60.33g)	Height - Seated (Max)	15.00mm
	Voltage - Isolation	-
Report errors?	Weight	0.133 lb (60.33g)
		Report errors?

BV030-7186.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BV030-7186.0 Payment Methods



















BV030-7186.0 Shipping Methods













If you have any question about BV030-7186.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com