

BV030-7273.0 Information

Heisener.com

Part Number BV030-7273.0

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 1.2VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BV030-7273.0 Specifications

Manufacturer BV030-7273.0 Manufacturer Pulse Electronics Power Category Transformers Power Transformers - Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 24V Current - Output (Max) 50mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation -		
CategoryTransformersPackage-Series-TypeLaminated CoreVoltage - Primary230VVoltage - Secondary (Full Load)24VCurrent - Output (Max)50mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)24.00mmVoltage - Isolation-	Manufacturer Part Number	BV030-7273.0
Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 24V Current - Output (Max) 50mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation -	Manufacturer	Pulse Electronics Power
Package - Series - Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 24V Current - Output (Max) 50mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation	Category	Transformers
Series - Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 24V Current - Output (Max) 50mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation		Power Transformers
Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 24V Current - Output (Max) 50mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation -	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) Voltage - Isolation 24V 24V 24V 24V 24V 24V 24V 24	Series	-
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) Voltage - Isolation 24V Simple 12 VA No 24.00mm 24 Omm	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Size / Dimension Yoltage - Isolation 50mA 50mA 50mA 50mA 50mA 51mgle 70m 70m 70m 70m 70m 70m 70m 70	Voltage - Primary	230V
Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 1.2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) Voltage - Isolation -	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)24.00mmVoltage - Isolation-	Current - Output (Max)	50mA
Center TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)24.00mmVoltage - Isolation-	Primary Winding(s)	Single
Power - Max 1.2 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) Voltage - Isolation -	Secondary Winding(s)	Single
Mounting Type Through Hole PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation -	Center Tap	No
Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation -	Power - Max	1.2 VA
Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 24.00mm Voltage - Isolation -	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation 24.00mm -	Termination Style	PC Pin
Voltage - Isolation -	Size / Dimension	32.50mm L x 27.50mm W
-	Height - Seated (Max)	24.00mm
W.:-L.	Voltage - Isolation	-
weight 0.133 lb (60.33g)	Weight	0.133 lb (60.33g)
Report errors?		Report errors?

BV030-7273.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BV030-7273.0 Payment Methods



















BV030-7273.0 Shipping Methods













If you have any question about BV030-7273.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com