

BV030-7294.0

BV030-7294.0 Information

For Reference Only	Part Number	BV030-7294.0	
	Manufacturer	Pulse Electronics Power	
	Category	Transformers Power Transformers	75
	Description	XFRMR LAMINATED 2VA THRU HOLE	- 26
	Package	-	
		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Req



quest a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BV030-7294.0 Specifications

ManufacturerPulse Electronics PowerCategoryTransformersPackage-Package-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)12VCurrent - Output (Max)SingleSecondary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StyleS2.50mm L x 27.50mm WHeight - Seated (Max)-Voltage - Isolation-		
CategoryTransformersPackage-Package-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)12VCurrent - Output (Max)SinglePrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeDrongh HoleSize / DimensionS2.50mm L x 27.50mm WSize / Dimension-Voltage - Isolation-Weight0.133 lb (60.33g)	Manufacturer Part Number	BV030-7294.0
PackagePower TransformersPackage-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)12VCurrent - Output (Max)122mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StyleS2.50mm L x 27.50mm WSize / Dimension-Voltage - Isolation-Weight0.133 lb (60.33g)	Manufacturer	Pulse Electronics Power
Package-Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)12VCurrent - Output (Max)122mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StyleS20m L x 27.50mm WSize / Dimension32.50mn L x 27.50mm WVoltage - Isolation-Weight0.133 lb (60.33g)	Category	Transformers
Series-TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)12VCurrent - Output (Max)122mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StyleS250mm L x 27.50mm WSize / Dimension32.50mm L x 27.50mm WVoltage - Isolation-Weight0.133 lb (60.33g)		Power Transformers
TypeLaminated CoreYoltage - Primary115VVoltage - Secondary (Full Load)12VCurrent - Output (Max)122mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StyleS2.50mm L x 27.50mm WSize / Dimension27.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Package	-
Yoltage - Primary115VVoltage - Secondary (Full Load)12VCurrent - Output (Max)122mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StyleS2.50mm L x 27.50mm WSize / Dimension27.00mmHeight - Seated (Max)-Weight0.133 lb (60.33g)	Series	-
Voltage - Secondary (Full Load)12VCurrent - Output (Max)122mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight0.133 lb (60.33g)	Туре	Laminated Core
Current - Output (Max)122mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight0.133 lb (60.33g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight0.133 lb (60.33g)	Voltage - Secondary (Full Load)	12V
Secondary Winding(s)SingleCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight0.133 lb (60.33g)	Current - Output (Max)	122mA
Center TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight0.133 lb (60.33g)	Primary Winding(s)	Single
Power - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)27.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Secondary Winding(s)	Single
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)27.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Center Tap	No
Termination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)27.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Power - Max	2 VA
Size / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)27.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Mounting Type	Through Hole
Height - Seated (Max)27.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Termination Style	PC Pin
Voltage - Isolation-Weight0.133 lb (60.33g)	Size / Dimension	32.50mm L x 27.50mm W
Weight 0.133 lb (60.33g)	Height - Seated (Max)	27.00mm
	Voltage - Isolation	-
Report errors?	Weight	0.133 lb (60.33g)
		Report errors?

BV030-7294.0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BV030-7294.0 Payment Methods



BV030-7294.0 Shipping Methods



If you have any question about BV030-7294.0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com