

BV030-7333.0 Information

Heisener.com

Part Number BV030-7333.0

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 2.3VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BV030-7333.0 Specifications

Manufacturer BV030-7333.0 Manufacturer Pulse Electronics Power Category Transformers Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 96mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 29.00mm Voltage - Isolation - Report errors?		
Category Transformers Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 96mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 29.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer Part Number	BV030-7333.0
Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 96mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 29.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer	Pulse Electronics Power
Package - Series - Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 24 V Current - Output (Max) 96mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 29.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Category	Transformers
Series-TypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)24 VCurrent - Output (Max)96mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2.3 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)29.00mmVoltage - Isolation-Weight0.133 lb (60.33g)		Power Transformers
TypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)24 VCurrent - Output (Max)96mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max2.3 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)29.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Veight 115V 15V POM POM POM POM POM POM POM PO	Series	-
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style Size / Dimension PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Voltage - Isolation 0.133 lb (60.33g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Voltage - Isolation Voltage - Isolation Veight 96mA 96mA 96mA 96mA 96mA 96mA 96mA 96m	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Height - Seated (Max) Voltage - Isolation Veight Single Single No PO No 9.3 VA Through Hole PC Pin 32.50mm L x 27.50mm W 29.00mm - 0.133 lb (60.33g)	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapNoPower - Max2.3 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension32.50mm L x 27.50mm WHeight - Seated (Max)29.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Current - Output (Max)	96mA
Center Tap No Power - Max 2.3 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 29.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) Voltage - Isolation - Weight 2.3 VA 2.3 VA 2.4 VA 2.5 VA 2.5 VA 2.6 VA 2.7 VA 2.7 VA 2.7 VA 2.8 VA 2.8 VA 2.8 VA 2.9 VA 2	Secondary Winding(s)	Single
Mounting Type Through Hole PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 29.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Center Tap	No
Termination Style PC Pin Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 29.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Power - Max	2.3 VA
Size / Dimension 32.50mm L x 27.50mm W Height - Seated (Max) 29.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 29.00mm - 0.133 lb (60.33g)	Termination Style	PC Pin
Voltage - Isolation - Weight 0.133 lb (60.33g)	Size / Dimension	32.50mm L x 27.50mm W
Weight 0.133 lb (60.33g)	Height - Seated (Max)	29.00mm
	Voltage - Isolation	-
Report errors?	Weight	0.133 lb (60.33g)
report errors.		Report errors?

BV030-7333.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BV030-7333.0 Payment Methods



















BV030-7333.0 Shipping Methods













If you have any question about BV030-7333.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com