

BV048-5058.0 Information

Heisener.com

Part Number BV048-5058.0

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 10VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part Number BV048-5058.0 Manufacturer Pulse Electronics Power Category Transformers Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 15V Current - Output (Max) 666mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)		
Category Transformers Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 15V Current - Output (Max) 666mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer Part Number	BV048-5058.0
Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 15V Current - Output (Max) 666mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer	Pulse Electronics Power
Package - Series - Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 15V Current - Output (Max) 666mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Category	Transformers
Series - Type Laminated Core Voltage - Primary 115 V Voltage - Secondary (Full Load) 15 V Current - Output (Max) 666mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 15V Current - Output (Max) 666mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Package	-
Voltage - Primary 115V Voltage - Secondary (Full Load) 15V Current - Output (Max) 666mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Series	-
Voltage - Secondary (Full Load) Current - Output (Max) 666mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension For Seated (Max) Voltage - Isolation Voltage - Isolation 15V 666mA 11V No Pingle No 10 VA No 10 VA 10 VA 10 VA 10 VA 11 VA 12 VA 13 VA 14 VA 15 VA 16 VA 17 VOIT VA 18 VOIT VA 18 VOIT VA 18 VOIT VA 19 VOIT VA 19 VOIT VA 10 VA 10 VA 11 VA 11 VA 12 VA 13 VA 14 VA 15 VA 16 VA 17 VA 18 VA 18 VA 19 VA 10 VA 1	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Size / Dimension Voltage - Isolation Voltage - Isolation Weight 666mA 66	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension Fixed (Max) Voltage - Isolation Veight Single Single Single No PO No No 10 VA Through Hole PC Pin Size / Dimension 50.50mm L x 42.50mm W 34.50mm Voltage - Isolation - Voltage - Isolation 0.133 lb (60.33g)	Voltage - Secondary (Full Load)	15V
Secondary Winding(s)SingleCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.50mm L x 42.50mm WHeight - Seated (Max)34.50mmVoltage - Isolation-Weight0.133 lb (60.33g)	Current - Output (Max)	666mA
Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) Voltage - Isolation - Weight 10 VA 10 VA 10 VA 10 VA 11 VA 12 VA 13 VA 14 VA 15 VA 16 VA 16 VA 17 VA 18 VA 18 VA 19 VA 19 VA 10 VA	Secondary Winding(s)	Single
Mounting Type Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Center Tap	No
Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Power - Max	10 VA
Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 34.50mm - 0.133 lb (60.33g)	Termination Style	PC Pin
Voltage - Isolation - Weight 0.133 lb (60.33g)	Size / Dimension	50.50mm L x 42.50mm W
Weight 0.133 lb (60.33g)	Height - Seated (Max)	34.50mm
	Voltage - Isolation	-
Report errors?	Weight	0.133 lb (60.33g)
		Report errors?

BV048-5058.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BV048-5058.0 Payment Methods



















BV048-5058.0 Shipping Methods













If you have any question about BV048-5058.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com