

BV048-5228.0 Information

Heisener.com

Part Number BV048-5228.0

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 10VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BV048-5228.0 Specifications

Manufacturer BV048-5228.0 Manufacturer Pulse Electronics Power Category Transformers Power Transformers - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 416mA, Series 208mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)		
Category Transformers Power Transformers Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 416mA, Series 208mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer Part Number	BV048-5228.0
Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 416mA, Series 208mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer	Pulse Electronics Power
Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 416mA, Series 208mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Category	Transformers
Series-TypeLaminated CoreVoltage - Primary230VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 416mA, Series 208mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.50mm L x 42.50mm WHeight - Seated (Max)34.50mmVoltage - Isolation-Weight0.133 lb (60.33g)		Power Transformers
Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 416mA, Series 208mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 416mA, Series 208mA Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Found (Max) Voltage - Isolation Voltage - Isolation Voltage - Isolation Voltage - Isolation 0.133 lb (60.33g)	Series	-
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 24V, Series 48V Current - Output (Max) Parallel 416mA, Series 208mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Voltage - Isolation 0.133 lb (60.33g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Voltage - Isolation Voltage - Isolation Vinding Single Single No Pull No Pull No Power No	Voltage - Primary	230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Veight Single Single No No No Powal No PO No Single No No No Single No No Single No No No Single No No No Single No No Single No No Single No No No Single No Single No No Single No Si	Voltage - Secondary (Full Load)	Parallel 24V, Series 48V
Secondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.50mm L x 42.50mm WHeight - Seated (Max)34.50mmVoltage - Isolation-Weight0.133 lb (60.33g)	Current - Output (Max)	Parallel 416mA, Series 208mA
Center TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension50.50mm L x 42.50mm WHeight - Seated (Max)34.50mmVoltage - Isolation-Weight0.133 lb (60.33g)	Primary Winding(s)	Single
Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Center Tap	No
Termination Style PC Pin Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Power - Max	10 VA
Size / Dimension 50.50mm L x 42.50mm W Height - Seated (Max) 34.50mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 34.50mm - 0.133 lb (60.33g)	Termination Style	PC Pin
Voltage - Isolation - Weight 0.133 lb (60.33g)	Size / Dimension	50.50mm L x 42.50mm W
Weight 0.133 lb (60.33g)	Height - Seated (Max)	34.50mm
	Voltage - Isolation	-
Report errors?	Weight	0.133 lb (60.33g)
Tepott offolis.		Report errors?

BV048-5228.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BV048-5228.0 Payment Methods



















BV048-5228.0 Shipping Methods













If you have any question about BV048-5228.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com