

BV054-5193.0 Information

Heisener.com

Part Number BV054-5193.0

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 16VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BV054-5193.0 Specifications

Manufacturer Part Number BV054-5193.0 Manufacturer Pulse Electronics Power Category Transformers Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 12V Current - Output (Max) 1.333A Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)		
Category Transformers Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 12V Current - Output (Max) 1.333A Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer Part Number	BV054-5193.0
Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 12V Current - Output (Max) 1.333A Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Manufacturer	Pulse Electronics Power
Package - Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 12V Current - Output (Max) 1.333A Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Category	Transformers
Series - Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 12V Current - Output (Max) 1.333A Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)		Power Transformers
Type Laminated Core Voltage - Primary 230V Voltage - Secondary (Full Load) 12V Current - Output (Max) 1.333A Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Package	-
Voltage - Primary 230V Voltage - Secondary (Full Load) 12V Current - Output (Max) 1.333A Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Series	-
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style Size / Dimension From Size / Dimension Voltage - Isolation Voltage - Isolation Weight 1.333A 1.333A Single No Pome No 16 VA No 16 VA 16 VA 16 VA 17 Through Hole PC Pin 18 Size / Dimension 19 0.133 lb (60.33g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Formination Size - Seated (Max) Voltage - Isolation Voltage - Isolation 1.333A 1.333A 1.333A 1.333A 1.333A 1.333A No No 16 VA No 16 VA 16 VA 16 VA 17 Through Hole PC Pin 57.00mm L x 48.00mm W 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Voltage - Primary	230V
Primary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Height - Seated (Max) Voltage - Isolation Veight Single Single No PO No Power - Max 16 VA Through Hole PC Pin S7.00mm L x 48.00mm W 39.00mm Voltage - Isolation - Voltage - Isolation 0.133 lb (60.33g)	Voltage - Secondary (Full Load)	12V
Secondary Winding(s)SingleCenter TapNoPower - Max16 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.00mm L x 48.00mm WHeight - Seated (Max)39.00mmVoltage - Isolation-Weight0.133 lb (60.33g)	Current - Output (Max)	1.333A
Center Tap No Power - Max 16 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) Voltage - Isolation Veight 16 VA PC Pin 57.00mm L x 48.00mm W 39.00mm 0.133 lb (60.33g)	Secondary Winding(s)	Single
Mounting Type Through Hole PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) Voltage - Isolation - Weight O.133 lb (60.33g)	Center Tap	No
Termination Style PC Pin Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Power - Max	16 VA
Size / Dimension 57.00mm L x 48.00mm W Height - Seated (Max) 39.00mm Voltage - Isolation - Weight 0.133 lb (60.33g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 39.00mm - 0.133 lb (60.33g)	Termination Style	PC Pin
Voltage - Isolation - Weight 0.133 lb (60.33g)	Size / Dimension	57.00mm L x 48.00mm W
Weight 0.133 lb (60.33g)	Height - Seated (Max)	39.00mm
	Voltage - Isolation	-
Report errors?	Weight	0.133 lb (60.33g)
		Report errors?

BV054-5193.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BV054-5193.0 Payment Methods



















BV054-5193.0 Shipping Methods













If you have any question about BV054-5193.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com