

BYT28-500,127

BYT28-500,127 Information



Part Number	BYT28-500,127	
Manufacturer	WeEn Semiconductors	
Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays	
Description	DIODE ARRAY GP 500V 10A TO220AB	
Package	TO-220-3	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdart@heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BYT28-500,127 Specifications

Manufacturer WeEn Semiconductors Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Diodes - Rectifiers - Arrays Package TO-220-3 Series - Diode Configuration 1 Pair Common Cathode Diode Type Standard Voltage - DC Reverse (Vr) (Max) 500V Current - Average Rectified (Io) (per Diode) 10A Voltage - Forward (Vf) (Max) @ If 1.4V @ 10A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 60ns Current - Reverse Leakage @ Vr 10µA @ 500V Operating Temperature - Junction 150°C (Max) Mounting Type Through Hole Package / Case TO-220-3		
CategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)500VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10µA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Manufacturer Part Number	BYT28-500,127
Diodes - Rectifiers - ArraysPackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)500VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10µA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220AB	Manufacturer	WeEn Semiconductors
PackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)500VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10µA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Category	Discrete Semiconductor Products
Series-Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)500VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10µA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220AB		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)500VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10µA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Package	TO-220-3
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)500VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Speed60nsCurrent - Reverse Leakage @ Vr10µA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Series	-
Voltage - DC Reverse (Vr) (Max)500VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10µA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10µA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.4V @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10μA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Voltage - DC Reverse (Vr) (Max)	500V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10μA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Current - Average Rectified (Io) (per Diode)	10A
Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10μA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Voltage - Forward (Vf) (Max) @ If	1.4V @ 10A
Current - Reverse Leakage @ Vr10μA @ 500VOperating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction150°C (Max)Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Reverse Recovery Time (trr)	60ns
Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Current - Reverse Leakage @ Vr	10µA @ 500V
Package / CaseTO-220-3Supplier Device PackageTO-220AB	Operating Temperature - Junction	150°C (Max)
Supplier Device Package TO-220AB	Mounting Type	Through Hole
	Package / Case	TO-220-3
Report errors?	Supplier Device Package	TO-220AB
		Report errors?

BYT28-500,127 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BYT28-500,127 Payment Methods



BYT28-500,127 Shipping Methods



If you have any question about BYT28-500,127, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com