

BYV415W-600PQ

BYV415W-600PQ Information

ewww.heisbaer.com	Part Number	BYV415W-600PQ
	Manufacturer	WeEn Semiconductors
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays
	Description	DIODE GEN PURP 600V 15A TO247
	Package	TO-247-3
		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BYV415W-600PQ Specifications

ManufacturerWeEn SemiconductorsCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysDiodes - Rectifiers - ArraysPackageTO-247-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If2.1V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10µA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageTO-247-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If2.1V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10µA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Manufacturer Part Number	BYV415W-600PQ
Diodes - Rectifiers - ArraysPackageTO-247-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If2.1V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10µA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Manufacturer	WeEn Semiconductors
PackageTO-247-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If2.1V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10 μ A @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Category	Discrete Semiconductor Products
Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If2.1V @ 15ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10µA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If2.1V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10µA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Package	TO-247-3
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max) $600V$ Current - Average Rectified (Io) (per Diode) $15A$ Voltage - Forward (Vf) (Max) @ If $2.1V @ 15A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $45ns$ Current - Reverse Leakage @ Vr $10\mu A @ 600V$ Operating Temperature - Junction $-65^{\circ}C ~ 175^{\circ}C$ Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Series	-
Voltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If2.1V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10µA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If $2.1V @ 15A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $45ns$ Current - Reverse Leakage @ Vr $10\mu A @ 600V$ Operating Temperature - Junction $-65^{\circ}C ~ 175^{\circ}C$ Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If2.1V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10μA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Voltage - DC Reverse (Vr) (Max)	600V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10μA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Current - Average Rectified (Io) (per Diode)	15A
Reverse Recovery Time (trr)45nsCurrent - Reverse Leakage @ Vr10μA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Voltage - Forward (Vf) (Max) @ If	2.1V @ 15A
Current - Reverse Leakage @ Vr10μA @ 600VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Reverse Recovery Time (trr)	45ns
Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247-3	Current - Reverse Leakage @ Vr	10µA @ 600V
Package / CaseTO-247-3Supplier Device PackageTO-247-3	Operating Temperature - Junction	-65°C ~ 175°C
Supplier Device Package TO-247-3	Mounting Type	Through Hole
	Package / Case	TO-247-3
Report errors?	Supplier Device Package	TO-247-3
		Report errors?

BYV415W-600PQ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BYV415W-600PQ Payment Methods





If you have any question about BYV415W-600PQ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com