



## C0402C132F3JAC7867 Information



For Reference Only

Part Number C0402C132F3JAC7867

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

**Description** CAP CER 1300PF 25V U2J 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# C0402C132F3JAC7867 Specifications

Manufacturer Part Number         C0402C132F3JAC7867           Manufacturer         KEMET           Category         Capacitors           Package         0402 (1005 Metric)           Series         C           Capacitance         1300pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -		
Category         Capacitors           Package         0402 (1005 Metric)           Series         C           Capacitance         1300pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)	Manufacturer Part Number	C0402C132F3JAC7867
Package         0402 (1005 Metric)           Series         C           Capacitance         1300pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)	Manufacturer	KEMET
Package         0402 (1005 Metric)           Series         C           Capacitance         1300pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)	Category	Capacitors
Series         C           Capacitance         1300pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)		Ceramic Capacitors
Capacitance         1300pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)	Package	0402 (1005 Metric)
Tolerance ±1%  Voltage - Rated 25V  Temperature Coefficient U2J  Operating Temperature -55°C ~ 125°C  Features Low Dissipation Factor, Low ESL  Ratings -  Applications General Purpose  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric)  Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max) -  Thickness (Max) 0.022" (0.55mm)	Series	C
Voltage - Rated  Temperature Coefficient  U2J  Operating Temperature  -55°C ~ 125°C  Features  Low Dissipation Factor, Low ESL  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  0402 (1005 Metric)  Size / Dimension  0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max)  Thickness (Max)  0.022" (0.55mm)	Capacitance	1300pF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  Low Dissipation Factor, Low ESL  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  0402 (1005 Metric)  Size / Dimension  0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max)  Thickness (Max)  0.022" (0.55mm)	Tolerance	±1%
Operating Temperature  -55°C ~ 125°C  Features  Low Dissipation Factor, Low ESL  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  0402 (1005 Metric)  Size / Dimension  0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max)  Thickness (Max)  -  0.022" (0.55mm)	Voltage - Rated	25V
Features Low Dissipation Factor, Low ESL  Ratings - Applications General Purpose  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric)  Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm)	Temperature Coefficient	U2J
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm)	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm)	Features	Low Dissipation Factor, Low ESL
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm)	Applications	General Purpose
Package / Case       0402 (1005 Metric)         Size / Dimension       0.039" L x 0.020" W (1.00mm x 0.50mm)         Height - Seated (Max)       -         Thickness (Max)       0.022" (0.55mm)	Failure Rate	-
Size / Dimension       0.039" L x 0.020" W (1.00mm x 0.50mm)         Height - Seated (Max)       -         Thickness (Max)       0.022" (0.55mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  - 0.022" (0.55mm)	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.022" (0.55mm)	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
	Height - Seated (Max)	-
Lead Spacing -	Thickness (Max)	0.022" (0.55mm)
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

## C0402C132F3JAC7867 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## C0402C132F3JAC7867 Payment Methods



















# C0402C132F3JAC7867 Shipping Methods













If you have any question about C0402C132F3JAC7867, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com