



### C0402H152J5GAC7867 Information

www.handar.com

For Reference Only

Part Number C0402H152J5GAC7867

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

**Description** CAP CER 1500PF 50V C0G/NP0 0402

**Package** 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# C0402H152J5GAC7867 Specifications

Manufacturer Part NumberC0402H152J5GAC7867ManufacturerKEMETCategoryCapacitorsPackage0402 (1005 Metric)SeriesHCapacitance1500pFTolerance±5%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 200°CFeaturesLow ESL, High TemperatureRatings-ApplicationsDownholeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)
Category         Capacitors           Package         0402 (1005 Metric)           Series         H           Capacitance         1500pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 200°C           Features         Low ESL, High Temperature           Ratings         -           Applications         Downhole           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)
Ceramic CapacitorsPackage0402 (1005 Metric)SeriesHCapacitance1500pFTolerance±5%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 200°CFeaturesLow ESL, High TemperatureRatings-ApplicationsDownholeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)
Package 0402 (1005 Metric) Series H Capacitance 1500pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 200°C Features Low ESL, High Temperature Ratings - Applications Downhole Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0400 (1005 Metric)
SeriesHCapacitance1500pFTolerance±5%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 200°CFeaturesLow ESL, High TemperatureRatings-ApplicationsDownholeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)
Capacitance 1500pF  Tolerance ±5%  Voltage - Rated 50V  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 200°C  Features Low ESL, High Temperature  Ratings - Applications Downhole  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric)
Tolerance ±5%  Voltage - Rated 50V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 200°C  Features Low ESL, High Temperature  Ratings - Applications Downhole  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric)
Voltage - Rated  Temperature Coefficient  COG, NP0  Operating Temperature  -55°C ~ 200°C  Features  Low ESL, High Temperature  Ratings  - Applications  Downhole  Failure Rate  Mounting Type  Surface Mount, MLCC  Package / Case  50V  COG, NP0  -55°C ~ 200°C  Low ESL, High Temperature  - Surface Mount, MLCC  0402 (1005 Metric)
Temperature Coefficient  Operating Temperature  -55°C ~ 200°C  Features  Low ESL, High Temperature  Ratings  - Applications  Downhole  Failure Rate  Mounting Type  Surface Mount, MLCC  Package / Case  O402 (1005 Metric)
Operating Temperature -55°C ~ 200°C Features Low ESL, High Temperature Ratings - Applications Downhole Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric)
Features Low ESL, High Temperature  Ratings - Applications Downhole  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric)
Ratings - Applications Downhole Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric)
Applications Downhole Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric)
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric)
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric)
Package / Case 0402 (1005 Metric)
-
Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm)
Height - Seated (Max)
Thickness (Max) 0.022" (0.55mm)
Lead Spacing -
Lead Style -
Report errors?

#### C0402H152J5GAC7867 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## C0402H152J5GAC7867 Payment Methods



















# C0402H152J5GAC7867 Shipping Methods













If you have any question about C0402H152J5GAC7867, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com