

C0603C392M8JAC7867

C0603C392M8JAC7867 Information



For Reference Only

Part Number	C0603C392M8JAC7867	
Manufacturer	KEMET	
Category	Capacitors Ceramic Capacitors	
Description	CAP CER 3900PF 10V U2J 0603	
Package	0603 (1608 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C0603C392M8JAC7867 Specifications

ManufacturerKEMETCacacitorsPackageCeramic CapacitorsPackage6003 (1608 Metric)SeriesCCapacitance900pFTolerance±20%Voltage - Rated10VTomperature CoefficientU2JOperating Temperature55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSuface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.663° L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Tickness (Max)0.034" (0.87mm)Lead Spacing-Starting-Starting (Suface)-Starting (Suface		
CategoryCapacitorsPackage6003 (1608 Metric)Package6003 (1608 Metric)SeriesCCapacitance3900pFTolerance±20%Voltage - Rated10VOperating Temperature CoefficientU2JOperating Temperature55°C ~ 125°CPattersLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0.063' (La 0.032'' W (1.60mm x 0.80mm)Size / Dimension0.063'' La 0.032'' W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034'' (0.87mm)Lead Spacing-Lead Syle-Lead Syle-Start Component-Start Component	Manufacturer Part Number	C0603C392M8JAC7867
Ceramic CapacitorsPackage0603 (1608 Metric)SeriesCCapacitance3900pFTolerance±20%Voltage - Rated10VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Manufacturer	KEMET
Package0603 (1608 Metric)SeriesCCapacitance3900pFTolerance±20%Voltage - Rated10VTomperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Category	Capacitors
SeriesCCapacitance3900pFTolerance±20%Voltage - Rated10VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance3900pFTolerance±20%Voltage Rated10VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Package	0603 (1608 Metric)
Tolerance±20%Voltage - Rated10VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Style-	Series	C
Voltage - Rated10VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Capacitance	3900pF
Temperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Voltage - Rated	10V
FeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Head Style-	Temperature Coefficient	U2J
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Features	Low Dissipation Factor, Low ESL
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.034" (0.87mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.034" (0.87mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Package / Case	0603 (1608 Metric)
Thickness (Max)0.034" (0.87mm)Lead Spacing-Lead Style-	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.80mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.034" (0.87mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C0603C392M8JAC7867 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C0603C392M8JAC7867 Payment Methods



If you have any question about C0603C392M8JAC7867, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com