



C0603X152J3JAC7867 Information



For Reference Only

Part Number C0603X152J3JAC7867

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 1500PF 25V U2J 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C0603X152J3JAC7867 Specifications

Manufacturer Part Number C0603X152J3JAC7867 Manufacturer KEMET Category Capacitors Package 0603 (1608 Metric) Series FT-CAP Capacitance 1500pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm) Height - Seated (Max) -		
Category Capacitors Package 0603 (1608 Metric) Series FT-CAP Capacitance 1500pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Manufacturer Part Number	C0603X152J3JAC7867
Ceramic Capacitors Package 0603 (1608 Metric) Series FT-CAP Capacitance 1500pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Manufacturer	KEMET
Package0603 (1608 Metric)SeriesFT-CAPCapacitance1500pFTolerance±5%Voltage - Rated25 VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)	Category	Capacitors
SeriesFT-CAPCapacitance1500pFTolerance±5%Voltage - Rated25VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.80mm)		Ceramic Capacitors
Capacitance 1500pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 1500pF 25V Applications - Dimension 1500pF 1000pF 1	Package	0603 (1608 Metric)
Tolerance ±5% Voltage - Rated 25V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Series	FT-CAP
Voltage - Rated Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 25V U2J -55°C ~ 125°C -55°C ~ 125°C -50°C -50°C ~ 125°C -50°C -50°C ~ 125°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -125°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -50°C -60°C	Capacitance	1500pF
Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension U2J Soft Termination Soft Termination - Mounting Type Boardflex Sensitive - 0003 "L x 0.032" W (1.60mm x 0.80mm)	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Voltage - Rated	25V
Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Temperature Coefficient	U2J
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Applications	Boardflex Sensitive
Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Failure Rate	-
Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.80mm)	Mounting Type	Surface Mount, MLCC
	Package / Case	0603 (1608 Metric)
Height - Seated (Max) -	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.80mm)
	Height - Seated (Max)	-
Thickness (Max) 0.034" (0.87mm)	Thickness (Max)	0.034" (0.87mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

C0603X152J3JAC7867 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C0603X152J3JAC7867 Payment Methods



















C0603X152J3JAC7867 Shipping Methods













If you have any question about C0603X152J3JAC7867, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com