



C0603X5R1H331K Information



For Reference Only

Part Number C0603X5R1H331K Manufacturer TDK Corporation Category

Capacitors

Ceramic Capacitors

Description CAP CER 330PF 50V X5R 0201

Package 0201 (0603 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C0603X5R1H331K Specifications

Manufacturer Part Number C0603X5R1H331K Manufacturer TDK Corporation Category Capacitors Package 0201 (0603 Metric) Series C Capacitance 330pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0201 (0603 Metric) Series C Capacitance 330pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Manufacturer Part Number	C0603X5R1H331K
Package 0201 (0603 Metric) Series C Capacitance 330pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Manufacturer	TDK Corporation
Package 0201 (0603 Metric) Series C Capacitance 330pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Category	Capacitors
Series C Capacitance 330pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 330pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Package	0201 (0603 Metric)
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Series	C
Voltage - Rated50VTemperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Capacitance	330pF
Temperature Coefficient N5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style - **Size / Dimension	Tolerance	±10%
Operating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Temperature Coefficient	X5R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	0201 (0603 Metric)
Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Size / Dimension	0.024" L x 0.012" W (0.60mm x 0.30mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.013" (0.33mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C0603X5R1H331K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C0603X5R1H331K Payment Methods



















C0603X5R1H331K Shipping Methods













If you have any question about C0603X5R1H331K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com