

C0805C332J4RACTU

C0805C332J4RACTU Information



For Reference Only

Part Number	C0805C332J4RACTU	
Manufacturer	KEMET	
Category	Capacitors Ceramic Capacitors	
Description	CAP CER 3300PF 16V X7R 0805	
Package	0805 (2012 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C0805C332J4RACTU Specifications

CategoryCapacitorsPackage0805 (2012 Metric)Package0805 (2012 Metric)SeriesCCapacitance3300pFTolerance±5% CategoryVoltage - Rated16VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CPacturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-		
CategoryCapacitorsPackage0805 (2012 Metric)Series0805 (2012 Metric)Capacitance3300pFCapacitance±5%Yoltage - Rated16VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CPattings-0ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.35" (0.88mm)Lead Spacing-Lead Syle-	Manufacturer Part Number	C0805C332J4RACTU
Ceramic CapacitorsPackage0805 (2012 Metric)SeriesCCapacitance3300pFTolerance±5%Voltage - Rated16VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.037" (L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Manufacturer	KEMET
Package0805 (2012 Metric)SeriesCCapacitance3300pFTolerance±5%Voltage - Rated16VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeS05 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Hickness (Max)-Lead Spacing-Lead Style-Lead Style-Lead Style-	Category	Capacitors
SeriesCCapacitance3300pFTolerance±5%Voltage - Rated16VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance3300pFTolerance±5%Voltage - Rated16VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Package	0805 (2012 Metric)
Tolerance±5%Voltage - Rated16VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.035" (0.88mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Series	С
Voltage - Rated16VTemperature CoefficientX7ROperating Temperature-5°C ~ 125°CFeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Lead Spacing0.035" (0.88mm)Lead Spacing-Lead Style-	Capacitance	3300pF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-Strace Mount, Marce-Strace Mount, Ma	Tolerance	$\pm 5\%$
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Kead Style-Lead Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-Styl	Voltage - Rated	16V
FeaturesLow ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Height Seated (Max)-Case-Starter (Max)-Starter (Max)-S	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Features	Low ESL
Failure Rate-Failure RateSurface Mount, MLCCMounting Type0805 (2012 Metric)Package / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Applications	General Purpose
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Package / Case	0805 (2012 Metric)
Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.88mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C0805C332J4RACTU Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C0805C332J4RACTU Payment Methods



If you have any question about C0805C332J4RACTU, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com