

C0805C912M4JAC7800

C0805C912M4JAC7800 Information



For Reference Only

Part Number	C0805C912M4JAC7800	
Manufacturer	KEMET	
Category	Capacitors Ceramic Capacitors	
Description	CAP CER 9100PF 16V U2J 0805	
Package	0805 (2012 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

C0805C912M4JAC7800 Specifications

Manufacturer Part Number C0805C912M4JAC7800 Manufacturer KEMET Category Capacitors Package 0805 (2012 Metric) Package 0805 (2012 Metric) Series C Capacitance 9100pF Tolerance ±20% Voltage - Rated 16V Operating Temperature 025°C ~ 125°C Operating Temperature 55°C ~ 125°C Pactage Low Dissipation Factor, Low ESL Applications General Purpose Faiture Rate - Mounting Type Soft (2012 Metric) Size / Dimension 0079° L x 0.049° W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.035° (0.88mm) Lead Spacing - Lead Spacing -		
CategoryCapacitorsPackage805 (2012 Metric)SeriesCCapacitance9100pFTolerance±20%Voltage - Rated16VTomperature Coefficient12JOperating Temperature55°C ~ 125°CFeaturesCoursispation Factor, Low ESLRatings-ApplicationsSenderal MuntersFailure Rate-Mounting TypeSub (2012 Metric)Package / Case0805 (2012 Metric)Size / Dimension0.070° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Height - Seated (Max)0.35″ (0.88mm)Lead Spacing-Lead Style-	Manufacturer Part Number	C0805C912M4JAC7800
Ceramic CapacitorsPackage0805 (2012 Metric)SeriesCCapacitance9100pFTolerance±20%Voltage - Rated16VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate.Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension.Height - Seated (Max).Height - Seated (Max).Lead Spacing.Lead Style.	Manufacturer	KEMET
Package0805 (2012 Metric)SeriesCCapacitance9100pFTolerance±20%Voltage - Rated16VTemperature CoefficientU2JOperating Temperature>5°° C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Nounting TypeSufface Mount, MLCCPackage / Case0.007° L x 0.049° W (2.00mm x 1.25mm)Size / Dimension0.035° (0.88mm)Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Category	Capacitors
SeriesCCapacitance9100pFTolerance±20%Voltage - Rated16VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Spacing-Lead Style-Style <t< td=""><td></td><td>Ceramic Capacitors</td></t<>		Ceramic Capacitors
Capacitance9100pFTolerance±20%Voltage - Rated16VTemperature CoefficientUJOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.079° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.35° (0.88mm)Lead Spacing-Lead Style-	Package	0805 (2012 Metric)
Tolerance±20%Voltage - Rated16VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Series	С
Voltage - RatedI6VTemperature CoefficientU2JOperating Temperature-5°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-St	Capacitance	9100pF
Temperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Spacing0.35" (0.88mm)Lead Spacing-Stare Spacing-Lead Style-Stare Spacing-Stare Spacing- </td <td>Tolerance</td> <td>±20%</td>	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
FeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Height - Seated (Max)-State Application-State Application-St	Temperature Coefficient	U2J
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Features	Low Dissipation Factor, Low ESL
Failure Rate-Failure RateSurface Mount, MLCCMounting Type0805 (2012 Metric)Package / Case0.079" L x 0.049" W (2.00mm x 1.25mm)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Applications	General Purpose
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.88mm)
· · · · · · · · · · · · · · · · · · ·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C0805C912M4JAC7800 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C0805C912M4JAC7800 Payment Methods





If you have any question about C0805C912M4JAC7800, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com