



C091 31C008 100 2 Information



For Reference Only

Part Number C091 31C008 100 2

Manufacturer Amphenol Sine Systems Corp

Category Connectors, Interconnects
Circular Connectors

Description CONN MALE RCPT 8POS REAR MT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C091 31C008 100 2 Specifications

Manufacturer Part Number C091 31C008 100 2 Manufacturer Amphenol Sine Systems Corp Category Connectors, Interconnects Package - Series C 091 D Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert DIN (270 Degree) Shell Size, MIL - Mounting Type Panel Mount Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100V Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series C 091 D Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert DIN (270 Degree) Shell Size, MIL - Mounting Type Panel Mount Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated Current Rating 5 A	Manufacturer Part Number	C091 31C008 100 2
Package-SeriesC 091 DConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertDIN (270 Degree)Shell Size, MIL-Mounting TypePanel MountTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VCurrent Rating5A	Manufacturer	Amphenol Sine Systems Corp
Package-SeriesC 091 DConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertDIN (270 Degree)Shell Size, MIL-Mounting TypePanel MountTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VCurrent Rating5A	Category	Connectors, Interconnects
SeriesC 091 DConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertDIN (270 Degree)Shell Size, MIL-Mounting TypePanel MountTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VCurrent Rating5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - InsertDIN (270 Degree)Shell Size, MIL-Mounting TypePanel MountTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VCurrent Rating5A	Package	-
Number of Positions8Shell Size - InsertDIN (270 Degree)Shell Size, MIL-Mounting TypePanel MountTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VCurrent Rating5A	Series	C 091 D
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100V Current Rating Shell Size - Insert Panel Mount Solder - Contact Finish Silver Features Shielded Toov Shell Material Shielded Solder Shielded Solder Shielded Solder Solde	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100V Current Rating 5A	Number of Positions	8
Mounting TypePanel MountTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VCurrent Rating5A	Shell Size - Insert	DIN (270 Degree)
Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100V Current Rating 5A	Shell Size, MIL	-
Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100V Current Rating 5A	Mounting Type	Panel Mount
Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100V Current Rating 5A	Termination	Solder
Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100V Current Rating 5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Shielded Voltage - Rated Current Rating Die Cast, Nickel Plated Silver Shielded 5A	Orientation	Keyed
Contact Finish Silver Features Shielded Voltage - Rated 100V Current Rating 5A	Ingress Protection	IP65/67 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated 100V Current Rating 5A	Shell Material, Finish	Die Cast, Nickel Plated
Voltage - Rated 100V Current Rating 5A	Contact Finish	Silver
Current Rating 5A	Features	Shielded
	Voltage - Rated	100V
Report errors?	Current Rating	5A
		Report errors?

C091 31C008 100 2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C091 31C008 100 2 Payment Methods





















C091 31C008 100 2 Shipping Methods













If you have any question about C091 31C008 100 2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com