

C091 31F004 100 2

Request a Quote

C091 31F004 100 2 Information

		C091 31F004 100 2 Amphenol Sine Systems Corp	
	Category	Connectors, Interconnects Circular Connectors	
	Description	CONN CIR FMALE 4POS R/A INLINE	
	Package	-	
		For the pricing/inventory/lead time, please contact us	LE192724.374
For Reference Only		Website: https://www.heisener.com	Decrease of Oracto

E-mail: salesdept@heisener.com

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C091 31F004 100 2 Specifications

ManufacturerAmphenol Sine Systems CorpCategoryConnectors, InterconnectsCircular ConnectorsCircular ConnectorsPackage-SeriesC 091 DConnector TypePlug, Female SocketsNumber of Positions4Shell Size - InsertDIN (210 Degree)Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupFastening TypeThreadedPortectionKeyedShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverSolder Strain ReliefSilverStoldage - RatedSilverStoldage - RatedSilver		
CategoryConnectors, InterconnectsCategoryConnectors, InterconnectsCackage-Package-SeriesC 091 DConnector TypePlug, Female SocketsNumber of Positions4Shell Size - InsertDIN (210 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupFastening TypeThreadedDirentationKeyedShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverContact FinishSilverVoltage - Rated300VCurrent RatingSA	Manufacturer Part Number	C091 31F004 100 2
Circular ConnectorsPackage-SeriesC 091 DConnector TypePlug, Female SocketsNumber of Positions4Shell Size - InsertDIN (210 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShelled, Strain ReliefVoltage - RatedSA	Manufacturer	Amphenol Sine Systems Corp
Package-SeriesC091 DConnector TypePlug, Female SocketsNumber of Positions4Shell Size - InsertDIN (210 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupPastening TypeThreadedDirentationKeyedIngress ProtectionDie Cast, Nickel PlatedShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesSileled, Strain ReliefVoltage - RatedSiONCurrent RatingSa	Category	Connectors, Interconnects
SeriesC 091 DConnector TypePlug, Female SocketsNumber of Positions4Shell Size - InsertDIN (210 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleFere Hanging (In-Line), Right AngleSolder CupFastening TypeThreadedDrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - InsertDIN (210 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionDie Cast, Nickel PlatedShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - RatedSolvCurrent RatingSA	Package	-
Number of Positions4Number of PositionsDIN (210 Degree)Shell Size - InsertDIN (210 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent RatingSA	Series	C 091 D
Shell Size - InsertDIN (210 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupFastening TypeThreadedDrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent RatingSA	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupFastening TypeThreadedOrientationKeyedDrientationIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent RatingSA	Number of Positions	4
Mounting TypeFree Hanging (In-Line), Right AngleFerminationSolder CupFastening TypeThreadedFastening TypeKeyedOrientationIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VSurrent RatingSA	Shell Size - Insert	DIN (210 Degree)
FerminationSolder CupFastening TypeThreadedDrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent RatingSA	Shell Size, MIL	-
Fastening TypeThreadedDrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent RatingSA	Mounting Type	Free Hanging (In-Line), Right Angle
DrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent RatingSA	Termination	Solder Cup
Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent RatingSA	Fastening Type	Threaded
Shell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent RatingSA	Orientation	Keyed
Contact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Ingress Protection	IP65/67 - Dust Tight, Water Resistant, Waterproof
FeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Shell Material, Finish	Die Cast, Nickel Plated
Voltage - Rated300VCurrent Rating5A	Contact Finish	Silver
Current Rating 5A	Features	Shielded, Strain Relief
-	Voltage - Rated	300V
Report errors?	Current Rating	5A
•		Report errors?

C091 31F004 100 2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C091 31F004 100 2 Payment Methods



C091 31F004 100 2 Shipping Methods



If you have any question about C091 31F004 100 2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com