



C091 31F006 101 2 Information

Heisener.com

Part Number C091 31F006 101 2

Manufacturer Amphenol Sine Systems Corp Category Connectors, Interconnects **Circular Connectors**

Description CONN PLUG 6POS INLINE RA SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C091 31F006 101 2 Specifications

Manufacturer Part Number C091 31F006 101 2 Manufacturer Amphenol Sine Systems Corp Category Connectors, Interconnects Package - Series C 091 D Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert DIN (240 Degree) Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A		
CategoryConnectors, InterconnectsPackage-SeriesC 091 DConnector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Manufacturer Part Number	C091 31F006 101 2
Package-SeriesC 091 DConnector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Manufacturer	Amphenol Sine Systems Corp
Package-SeriesC 091 DConnector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Category	Connectors, Interconnects
SeriesC 091 DConnector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert DIN (240 Degree) Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Package	-
Number of Positions6Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Series	C 091 D
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Number of Positions	6
Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated300VCurrent Rating5A	Shell Size - Insert	DIN (240 Degree)
Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Shell Size, MIL	-
Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Termination	Solder Cup
Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated Current Rating 5A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated Current Rating 5A	Orientation	Keyed
Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Ingress Protection	IP65/67 - Dust Tight, Water Resistant, Waterproof
Features Shielded, Strain Relief Voltage - Rated 300V Current Rating 5A	Shell Material, Finish	Die Cast, Nickel Plated
Voltage - Rated 300V Current Rating 5A	Contact Finish	Silver
Current Rating 5A	Features	Shielded, Strain Relief
-	Voltage - Rated	300V
Report errors?	Current Rating	5A
		Report errors?

C091 31F006 101 2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C091 31F006 101 2 Payment Methods



















C091 31F006 101 2 Shipping Methods













If you have any question about C091 31F006 101 2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com