



### C091 31H012 100 2 Information

**Part Number** C091 31H012 100 2

Manufacturer Amphenol Sine Systems Corp

Category Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 12POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **C091 31H012 100 2 Specifications**

Manufacturer Part Number       C091 31H012 100 2         Manufacturer       Amphenol Sine Systems Corp         Category       Connectors, Interconnects         Package       -         Series       C 091 D         Connector Type       Plug, Male Pins         Number of Positions       12         Shell Size - Insert       DIN         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       Keyed         Ingress Protection       IP65/67 - Dust Tight, Water Resistant, Waterproof         Shell Material, Finish       Die Cast, Nickel Plated         Contact Finish       Silver         Features       Shielded, Strain Relief         Voltage - Rated       150V         Current Rating       3A		
Category Connectors, Interconnects Circular Connectors  Package - Series C 091 D  Connector Type Plug, Male Pins Number of Positions 12 Shell Size - Insert DIN Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection P65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated Current Rating 3A	Manufacturer Part Number	C091 31H012 100 2
Package-SeriesC 091 DConnector TypePlug, Male PinsNumber of Positions12Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated150VCurrent Rating3A	Manufacturer	Amphenol Sine Systems Corp
Package-SeriesC 091 DConnector TypePlug, Male PinsNumber of Positions12Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated150VCurrent Rating3A	Category	Connectors, Interconnects
SeriesC 091 DConnector TypePlug, Male PinsNumber of Positions12Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated150VCurrent Rating3A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions12Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated150VCurrent Rating3A	Package	-
Number of Positions12Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated150VCurrent Rating3A	Series	C 091 D
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated  Contact Finish Silver Features Shielded, Strain Relief  Voltage - Rated 150V  Current Rating 3A	Number of Positions	12
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishDie Cast, Nickel PlatedContact FinishSilverFeaturesShielded, Strain ReliefVoltage - Rated150VCurrent Rating3A	Shell Size - Insert	DIN
Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 150V Current Rating 3A	Shell Size, MIL	-
Fastening Type Threaded Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 150V Current Rating 3A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Die Cast, Nickel Plated Contact Finish Silver Features Shielded, Strain Relief Voltage - Rated 150V Current Rating 3A	Termination	Solder Cup
Ingress Protection  IP65/67 - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish  Contact Finish  Silver  Features  Shielded, Strain Relief  Voltage - Rated  150V  Current Rating  3A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Shielded, Strain Relief  Voltage - Rated  Current Rating  3A	Orientation	Keyed
Contact Finish  Features  Shielded, Strain Relief  Voltage - Rated  Current Rating  3A	Ingress Protection	IP65/67 - Dust Tight, Water Resistant, Waterproof
Features Shielded, Strain Relief  Voltage - Rated 150V  Current Rating 3A	Shell Material, Finish	Die Cast, Nickel Plated
Voltage - Rated 150V Current Rating 3A	Contact Finish	Silver
Current Rating 3A	Features	Shielded, Strain Relief
	Voltage - Rated	150V
Report errors?	Current Rating	3A
		Report errors?

### C091 31H012 100 2 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## C091 31H012 100 2 Payment Methods



















### **C091 31H012 100 2 Shipping Methods**













If you have any question about C091 31H012 100 2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com