



## C1210C124F4JAC7800 Information

Part Number C1210C124F4JAC7800

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

**Description** CAP CER 0.12UF 16V U2J 1210

**Package** 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# C1210C124F4JAC7800 Specifications

Manufacturer Part Number         C1210C124F4JAC7800           Manufacturer         KEMET           Category         Capacitors           Package         1210 (3225 Metric)           Series         C           Capacitance         0.12μF           Tolerance         ±1%           Voltage - Rated         16V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.88mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         1210 (3225 Metric)           Series         C           Capacitance         0.12μF           Tolerance         ±1%           Voltage - Rated         16V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.88mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	C1210C124F4JAC7800
Package         1210 (3225 Metric)           Series         C           Capacitance         0.12µF           Tolerance         ±1%           Voltage - Rated         16V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.88mm)           Lead Spacing         -           Lead Style         -	Manufacturer	KEMET
Package         1210 (3225 Metric)           Series         C           Capacitance         0.12μF           Tolerance         ±1%           Voltage - Rated         16V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.88mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         C           Capacitance         0.12µF           Tolerance         ±1%           Voltage - Rated         16V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.88mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         0.12μF           Tolerance         ±1%           Voltage - Rated         16V           Temperature Coefficient         U2J           Operating Temperature         -55°C ~ 125°C           Features         Low Dissipation Factor, Low ESL           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1210 (3225 Metric)           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.035" (0.88mm)           Lead Spacing         -           Lead Style         -	Package	1210 (3225 Metric)
Tolerance ±1%  Voltage - Rated 16V  Temperature Coefficient U2J  Operating Temperature -55°C ~ 125°C  Features Low Dissipation Factor, Low ESL  Ratings -  Applications General Purpose  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 1210 (3225 Metric)  Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)  Height - Seated (Max) -  Thickness (Max) 0.035" (0.88mm)  Lead Spacing -  Lead Style -	Series	С
Voltage - Rated16VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Capacitance	0.12μF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  Low Dissipation Factor, Low ESL  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  1210 (3225 Metric)  Size / Dimension  0.126" L x 0.098" W (3.20mm x 2.50mm)  Height - Seated (Max)  Thickness (Max)  Lead Spacing  - Lead Style  -  U2J  023  025°C  120°C  120°C	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.035" (0.88mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features Low Dissipation Factor, Low ESL  Ratings - Applications General Purpose  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)  Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm)  Lead Spacing - Lead Style -	Temperature Coefficient	U2J
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style -	Features	Low Dissipation Factor, Low ESL
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case       1210 (3225 Metric)         Size / Dimension       0.126" L x 0.098" W (3.20mm x 2.50mm)         Height - Seated (Max)       -         Thickness (Max)       0.035" (0.88mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.126" L x 0.098" W (3.20mm x 2.50mm)         Height - Seated (Max)       -         Thickness (Max)       0.035" (0.88mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.035" (0.88mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.88mm)
	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

### C1210C124F4JAC7800 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### C1210C124F4JAC7800 Payment Methods



















## C1210C124F4JAC7800 Shipping Methods













If you have any question about C1210C124F4JAC7800, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com