



C1210C183F4JAC7800 Information

Part Number C1210C183F4JAC7800

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 0.018UF 16V U2J 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C1210C183F4JAC7800 Specifications

Manufacturer Part Number C1210C183F4JAC7800 Manufacturer KEMET Category Capacitors Package 1210 (3225 Metric) Series C Capacitance 0.018µF Tolerance ±1% Voltage - Rated 16V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Low Dissipation Factor, Low ESL Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.88mm)		
Category Capacitors Package 1210 (3225 Metric) Series C Capacitance 0.018μF Tolerance ±1% Voltage - Rated 16V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Low Dissipation Factor, Low ESL Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Manufacturer Part Number	C1210C183F4JAC7800
Package 1210 (3225 Metric) Series C Capacitance 0.018μF Tolerance ±1% Voltage - Rated 16V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Low Dissipation Factor, Low ESL Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Manufacturer	KEMET
Package1210 (3225 Metric)SeriesCCapacitance0.018μFTolerance±1%Voltage - Rated16VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-	Category	Capacitors
SeriesCCapacitance $0.018\mu F$ Tolerance $\pm 1\%$ Voltage - Rated $16V$ Temperature CoefficientU2JOperating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case $1210 (3225 \text{ Metric})$ Size / Dimension 0.126° L x 0.098° W $(3.20 \text{mm x } 2.50 \text{mm})$ Height - Seated (Max)-		Ceramic Capacitors
Capacitance0.018μFTolerance±1%Voltage - Rated16VTemperature CoefficientU2JOperating Temperature-55°C ~ 125°CFeaturesLow Dissipation Factor, Low ESLRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-	Package	1210 (3225 Metric)
Tolerance ±1% Voltage - Rated 16V Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Low Dissipation Factor, Low ESL Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Series	C
Voltage - Rated Temperature Coefficient U2J Operating Temperature -55°C ~ 125°C Features Low Dissipation Factor, Low ESL Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension Height - Seated (Max) - 16V U2J Capa General Purpose Low Dissipation Factor, Low ESL - County Esl - Cou	Capacitance	0.018μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low Dissipation Factor, Low ESL Ratings - Applications General Purpose Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension Height - Seated (Max) - U2J U2J 125°C Low Dissipation Factor, Low ESL Surface Mount, MLCC - 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Tolerance	$\pm 1\%$
Operating Temperature -55°C ~ 125°C Features Low Dissipation Factor, Low ESL Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Voltage - Rated	16V
Features Low Dissipation Factor, Low ESL Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Temperature Coefficient	U2J
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Features	Low Dissipation Factor, Low ESL
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Applications	General Purpose
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)	Package / Case	1210 (3225 Metric)
	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Thickness (Max) 0.035" (0.88mm)	Height - Seated (Max)	-
	Thickness (Max)	0.035" (0.88mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

C1210C183F4JAC7800 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C1210C183F4JAC7800 Payment Methods



















C1210C183F4JAC7800 Shipping Methods













If you have any question about C1210C183F4JAC7800, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com