

C14M8 Information



For Reference Only

Part Number C14M8
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 8A 690VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C14M8 Specifications

Manufacturer Part Number C14M8 Manufacturer Eaton Category Circuit Protection Package Cartridge, Non-Standard Series C14M Fuse Type Cartridge Current Rating 8A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesC14MFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC690VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Manufacturer Part Number	C14M8
Beckage Cartridge, Non-Standard Series C14M Fuse Type Cartridge Current Rating 8A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard C14M C1	Manufacturer	Eaton
Package Cartridge, Non-Standard Series C14M Fuse Type Cartridge Current Rating 8A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Category	Circuit Protection
SeriesC14MFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC690VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.008" L (14.30mm x 51.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating8AVoltage Rating - AC690VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 690V Voltage Rating - DC Response Time - Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8A 690V - 690V	Series	C14M
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 690V -	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Motor Protection Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Carridge, Non-Standard Size / Dimension - Operating Temperature Size / Dimension - Carridge, Non-Standard Operating Temperature Size / Dimension - Carridge, Non-Standard Operating Temperature Carridge, Operating Temperature Carridge, Non-Standard Operating Temperature Carridge, Operating Temperature Carridge, Operating Temperature Carridge, Operating Temperature Carridge, Operating Temperatur	Current Rating	8A
Response Time Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - Class - Cartridge, Non-Standard O.563" Dia x 2.008" L (14.30mm x 51.00mm)	Voltage Rating - AC	690V
Applications Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Voltage Rating - DC	-
Features - Class - Case - Coperating Temperature - Service - Case	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Applications	Motor Protection
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 0.563" Dia x 2.008" L (14.30mm x 51.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.008" L (14.30mm x 51.00mm)
		Report errors?

C14M8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C14M8 Payment Methods



















C14M8 Shipping Methods













If you have any question about C14M8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com