

C22G100S Information

Heisener.com

Part Number C22G100S

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE INDUST 100A CLASS GG

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C22G100S Specifications

Manufacturer Part Number C22G100S Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series - Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 500V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeries-Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Manufacturer Part Number	C22G100S
Backage Cartridge, Non-Standard Series - Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 500V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Sering Capacity (Pase) Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Sering Capacity (Pase) Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard	Manufacturer	Eaton
PackageCartridge, Non-StandardSeries-Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Category	Circuit Protection
Series-Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.866" Dia x 2.283" L (22.00mm x 58.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC Sonov Voltage Rating - DC Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 100A 500V 500V 500V - 500	Series	-
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 500V 500V	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cartridge, Non-Standard Size / Dimension - Cartridge, Non-Standard	Current Rating	100A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - Clectrical, Industrial Indicating Local Carting Capacity Features - Cartridge, Non-Standard O.866" Dia x 2.283" L (22.00mm x 58.00mm)	Voltage Rating - AC	500V
Applications Electrical, Industrial Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Voltage Rating - DC	-
Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Response Time	-
Class - Approvals - Coperating Temperature - Coperating Capacity @ Rated Voltage 120kA Holder Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Applications	Electrical, Industrial
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Class	-
Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Breaking Capacity @ Rated Voltage	120kA
Size / Dimension 0.866" Dia x 2.283" L (22.00mm x 58.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.866" Dia x 2.283" L (22.00mm x 58.00mm)
		Report errors?

C22G100S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C22G100S Payment Methods





















C22G100S Shipping Methods













If you have any question about C22G100S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com