

C22G2 Information



For Reference Only

Part Number C22G2 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 2A 690VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C22G2 Specifications

Manufacturer Part Number C22G2 Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series C22G Fuse Type Cartridge Current Rating 2A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesC22GFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC690VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Manufacturer Part Number	C22G2
Package Cartridge, Non-Standard Series C22G Fuse Type Cartridge Current Rating 2A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesC22GFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC690VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Category	Circuit Protection
SeriesC22GFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC690VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-Standard		Electrical, Specialty Fuses
Fuse Type Current Rating 2A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Cartridge 690V	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 690V Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case 2A 690V - Class - Response Time - Electrical, Industrial - Electrical, Industrial - Class - Class - Class - Class - Catrridge, Non-Standard	Series	C22G
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 690V - 690V	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case - Cartridge, Non-Standard	Current Rating	2A
Response Time - Applications Electrical, Industrial - Electrical, Industrial - Class -	Voltage Rating - AC	690V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard	Voltage Rating - DC	-
Features - Class - Class - Component of the Component of	Response Time	-
Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard	Applications	Electrical, Industrial
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard	Operating Temperature	-
Package / Case Cartridge, Non-Standard	Breaking Capacity @ Rated Voltage	80kA
	Mounting Type	Holder
Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Package / Case	Cartridge, Non-Standard
	Size / Dimension	0.874" Dia x 2.283" L (22.20mm x 58.00mm)
Report errors?		Report errors?

C22G2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C22G2 Payment Methods



















C22G2 Shipping Methods













If you have any question about C22G2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com