

C22G80S

C22G80S Information



For Reference Only

Part Number	C22G80S	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CRTRDGE 80A 500VAC NON STD	
Package	Cartridge, Non-Standard	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C22G80S Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesC22GFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMonting TypeHolderPackage / CaseCartridge, Non-Standard		
CategoryCircuit ProtectionPackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesC22GFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120KAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Manufacturer Part Number	C22G80S
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series C22G Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 500V Voltage Rating - DC - Applications Electrical, Industrial Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesC22GFuse TypeCartridgeFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeCartridge, Non-StandardPackage / CaseCartridge, Non-Standard	Category	Circuit Protection
SeriesC22GFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeFolderPackage / CaseCartridge, Non-Standard		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse Type80AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature120KABreaking Capacity @ Rated Voltage120kAPackage / CaseCartridge, Non-Standard	Package	Cartridge, Non-Standard
Current Rating80AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Series	C22G
Voltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Fuse Type	Cartridge
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Current Rating	80A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Voltage Rating - AC	500V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Voltage Rating - DC	-
FeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Response Time	-
Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Applications	Electrical, Industrial
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Class	-
Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-Standard	Approvals	-
Mounting TypeHolderPackage / CaseCartridge, Non-Standard	Operating Temperature	-
Package / Case Cartridge, Non-Standard	Breaking Capacity @ Rated Voltage	120kA
	Mounting Type	Holder
Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Package / Case	Cartridge, Non-Standard
	Size / Dimension	0.874" Dia x 2.283" L (22.20mm x 58.00mm)
Report errors?		Report errors?

C22G80S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about C22G80S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com