



C22M16S Information



For Reference Only

Part Number C22M16S Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 16A 690VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C22M16S Specifications

Manufacturer Part Number C22M16S Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series C22M Fuse Type Cartridge Current Rating 16A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesC22MFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC690VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Manufacturer Part Number	C22M16S
Backage Cartridge, Non-Standard Series C22M Fuse Type Cartridge Current Rating 16A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard C22M Cartridge, Non-Standard C22M Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer	Eaton
Package Cartridge, Non-Standard Series C22M Fuse Type Cartridge Current Rating 16A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Category	Circuit Protection
SeriesC22MFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC690VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.874" Dia x 2.283" L (22.20mm x 58.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 16A Voltage Rating - AC 690V Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Cartridge C	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 690V Voltage Rating - DC	Series	C22M
Voltage Rating - AC Voltage Rating - DC Response Time Applications Motor Protection Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 690V - 690V 690V - 690V	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cartridge, Non-Standard Size / Dimension - Operating Temperature - Operating Tempera	Current Rating	16A
Response Time Applications Motor Protection Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - Class - Control Protection And Prote	Voltage Rating - AC	690V
Applications Motor Protection Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Voltage Rating - DC	-
Features Indicating Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Applications	Motor Protection
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.874" Dia x 2.283" L (22.20mm x 58.00mm)
		Report errors?

C22M16S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C22M16S Payment Methods





















C22M16S Shipping Methods













If you have any question about C22M16S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com